

PRODUCT NO. 3679-1-B-Ware

DOTLUX LED safety light EXITtop with self-test incl. 2 interchangeable lenses white 3h B-goods



to the product page

- Replaceable rechargeable battery with a light duration of 3 hours
- Integrated control LED for operating status
- Only suitable for standby mode. If the light is supplied with mains power, the integrated rechargeable battery charges and the light is in stand-by mode.
- Incl. two easy-to-change lenses
 - Corridor lighting (asymmetrical)
 - Wide beam
- Automatic self-test function

WEIGHT IN KG 0.41
NET LUMINOUS FLUX IN LUMENS 240
POWER CONSUMPTION IN WATTS 0,5

BEAM ANGLE 180
PROTECTION CLASS (IP) IP20
INPUT VOLTAGE 220 - 240 V AC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 5000
POWER FACTOR 0,3
BATTERY RUNTIME 3h
PROTECTION CLASS II
INSTALLATION OPENING DIAMETER IN MM 120
INPUT VOLTAGE SPAN 220-240
WARRANTY IN YEARS 0
INPUT VOLTAGE RANGE LUMINAIRE 220-240
ETIM GRUPPEN-ID ECC001957

Dimensions

height: 62mm
diameter: 140mm