

PRODUCT NO. 4890-199036

DOTLUX LED tracklight SLIMtrack-eco max.21Watt POWERselect & COLORselect white 36°



to the product page

- LED tracklights have different power levels thanks to POWERselect
- Compatible with EUTRAC and almost all other 3-phase tracks
- Dimming function via phase cut-on/phase cut-off
- Adjustable color temperatures thanks to COLORselect
- Natural color perception thanks to extra high CRI value >92
- Suitable for simple installation in track rails
- Excellent price-performance ratio
- Sustainable product design thanks to easily replaceable components
- Passive cooling system without fan

| | |
|------------------------------------|----------------|
| SUCCESSION ARTICLE | - |
| PREDECESSOR ARTICLE | 4890-030036 |
| WEIGHT IN KG | 0.409 |
| POWER CONSUMPTION IN WATTS | 10/15/21 |
| NET LUMINOUS FLUX IN LUMENS | 1050/1450/2070 |
| LUMEN PER WATT | 105/104/104 |

Dimensions

length: 170mm
width: 65mm
height: 195mm
diameter: 65mm

| | |
|--|--------------------------|
| BEAM ANGLE | 36 |
| PROTECTION CLASS (IP) | IP20 |
| LIGHT COLOR | multicoloured |
| INPUT VOLTAGE | 186 - 240 AC/DC |
| SERVICE LIFE | approx. 50.000 h at 25°C |
| COLOR TEMPERATURE IN KELVIN | 2700/3200/4000 |
| COLOR-RENDERING-INDEX | CRI > 92 |
| POWER FACTOR | 0,9 |
| IK PROTECTION | IK05 |
| LUMEN PER WATT | 105/104/104 |
| PROTECTION CLASS | I |
| VOLTAGE TYPE | AC/DC |
| HOUSING COLOUR | white |
| INSTALLATION OPENING WIDTH IN MM | 0 |
| INSTALLATION OPENING DIAMETER IN MM | 65 |
| INSTALLATION OPENING LENGHT IN MM | 170 |
| INPUT VOLTAGE SPAN | 108-122 |
| WARRANTY IN YEARS | 3 |
| L80/B10 | 50000 |
| RATED CURRENT | 0.09 |
| SIMILAR TO RAL-COLOUR | 9016 |
| SUITABLE FOR SURFACE MOUNTING | Yes |
| SUITABLE FOR MOUNTING | No |
| DIMMING WITHOUT DIMMER | No |
| INPUT VOLTAGE RANGE LUMINAIRE | 108-122 |
| ASSORTMENT | Ecoline |

| | |
|--|----------------|
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| LIFETIME L80/B10 AT 25°C | 50000 |
| LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C | 75000 |
| ETIM GRUPPEN-ID | EC001744 |
| WITH ILLUMINANT | Yes |
| SUITABLE FOR WALL MOUNTING | Yes |
| SUITABLE FOR SUSPENDED MOUNTING | No |
| SUITABLE FOR CEILING MOUNTING | Yes |
| SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1 | No |
| SUITABLE FOR NUMBER OF LIGHT SOURCES | 1 |
| MATERIAL COVER | - |
| TYPE OF CONTROL GEAR | - |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | Yes |
| DIMMING DMX | Yes |
| DIMMING DSI | Yes |
| DIMMING POTENTIOMETER (INTEGRATED) | Yes |
| DIMMING LINESWITCH | Yes |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | Yes |
| DIMMING MAINS VOLTAGE MODULATION | Yes |
| DIMMING PHASE CUT-OFF | Yes |
| DIMMING PROGRAMMABLE | Yes |
| DIMMING RF | Yes |
| DIMMING SINE WAVE REDUCTION | Yes |
| DIMMING TOUCH AND DIM | Yes |
| DIMMING ZIGBEE | Yes |
| DIMMING WITH PUSH-BUTTON | Yes |
| DIMMING DEPENDING ON CONTROL GEAR | Yes |
| NO DIM FUNCTION | No |
| LIGHT DISTRIBUTOR | - |
| LIGHT SHARING | - |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| DEGREE OF PROTECTION (NEMA) | 1 |
| IMPACT STRENGTH | IK05 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| FILAMENT TEST ACCORDING TO IEC 60695-2-11 | 750 °C - 30 s |
| CONSTANT LIGHT OUTPUT (CLO) | Yes |
| TYPE OF WIRING | - |
| CONNECTION TYPE | Busbar adapter |
| PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 | RG1 |

| | |
|---|--------------------------|
| COLOUR OF LIGHT ADJUSTABLE | Positions |
| LUMINOUS FLUX ADJUSTABLE | Positions |
| BEAM ANGLE ADJUSTABLE | Positions |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | Yes |
| REFLECTOR | - |
| SUITABLE FOR LOW VOLTAGE CABLE SYSTEM | No |
| SUITABLE FOR CLAMP-MOUNTING | No |
| SUITABLE FOR LIGHT-TRACK MOUNTING | Yes |
| SUITABLE FOR PEDESTAL/FLOOR MOUNTING | No |
| SUITABLE FOR TRAVERSE MOUNTING | No |
| EXCHANGEABLE CONTROL GEAR | Yes |
| SUITABLE FOR LAMP POWER IN W | 20 |
| LAMP TYPE | LED exchangeable |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| SURFACE BRUSHED | No |
| DIMMING DALI-2 | Yes |
| DIMMING PHASE CUT-ON | Yes |
| DIMMING GPRS | Yes |
| LIFETIME L70/B50 AT 25°C | 75000 |
| BEG FUNDING | Only relevant in Germany |
| DREH- /SCHWENKBAR | 355° / 90° |
| ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE | F |
| LIGHT OUTLET | Direct |
| ADJUSTABILITY | Rotating and swivelling |
| SURFACE PROTECTION | Powder coating |
| BEAM ANGLE | Medium beam 21-40° |
| LAMP HOLDER | Other |