

PRODUCT NO. 5071-199036

DOTLUX LED tracklight SLIMtrack-eco max.29W POWERselect & COLORselect black 36°



to the product page

- LED tracklights have different power levels thanks to POWERselect
- Compatible with EUTRAC and almost all other 3-phase tracks
- Adjustable color temperatures thanks to COLORselect
- Natural color perception thanks to extra high CRI value >92
- Suitable for simple installation in track rails
- Excellent price-performance ratio
- Sustainable product design thanks to easily replaceable components
- Passive cooling system without fan

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	5071-030036, 5071-040036
WEIGHT IN KG	0.58
POWER CONSUMPTION IN WATTS	21/26/29
NET LUMINOUS FLUX IN LUMENS	2010/2370/2670
LUMEN PER WATT	101/99/99

BEAM ANGLE	36
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	multicoloured
INPUT VOLTAGE	186 - 240 AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	2700/3200/4000
COLOR-RENDERING-INDEX	CRI > 92
POWER FACTOR	0,9
IK PROTECTION	IK05
LUMEN PER WATT	101/99/99
PROTECTION CLASS	II
VOLTAGE TYPE	AC/DC
HOUSING COLOUR	black
INSTALLATION OPENING WIDTH IN MM	0
INSTALLATION OPENING DIAMETER IN MM	0
INSTALLATION OPENING LENGHT IN MM	171
INPUT VOLTAGE SPAN	36
WARRANTY IN YEARS	3
L80/B10	50000
RATED CURRENT	0.14
SIMILAR TO RAL-COLOUR	9005
SUITABLE FOR SURFACE MOUNTING	No
SUITABLE FOR MOUNTING	No
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	36

Dimensions

height: 223mm
length: 171mm
diameter: 75mm

ASSORTMENT	Ecoline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	75000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	No
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
SUITABLE FOR NUMBER OF LIGHT SOURCES	0
LAMP HOLDER	-
MATERIAL COVER	-
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
DEGREE OF PROTECTION (NEMA)	1
IMPACT STRENGTH	IK05
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	Yes
TYPE OF WIRING	Ending
CONNECTION TYPE	Push-in clamp
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1

COLOUR OF LIGHT ADJUSTABLE	Positions
LUMINOUS FLUX ADJUSTABLE	Positions
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	No
SUITABLE FOR LIGHT-TRACK MOUNTING	Yes
SUITABLE FOR PEDESTAL/FLOOR MOUNTING	No
SUITABLE FOR TRAVERSE MOUNTING	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	20
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
SURFACE BRUSHED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	75000
BEG FUNDING	Only relevant in Germany
DREH- /SCHWENKBAR	355° / 90°
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	F
LIGHT OUTLET	Direct
BEAM ANGLE ADJUSTABLE	No
SURFACE PROTECTION	Lacquered
LIGHT SHARING	Symmetric
ADJUSTABILITY	Rotating and swivelling
BEAM ANGLE	Medium beam 21-40°
REFLECTOR	Other
TYPE OF CONTROL GEAR	Not required