

PRODUCT NO. 4833-OFW160-B-Ware

DOTLUX LED luminaire LUNAsilver-sensor Ø490mm 36W COLORselect IP44



to the product page

- Decorative ring made of high-quality brushed aluminum
- Comfortable atmosphere due to indirect light components
- Silent sensor function
- On/Off function to 100% light intensity via daylight sensor, then 0% light intensity
- Shadow-free light distribution with very stable PMMA cover IK07
- Constant light output due to large area aluminum core board
- Easy installation, thanks to through-wireable luminaire terminal block
- Sustainable, repairable product design

WEIGHT IN KG	1.466
NET LUMINOUS FLUX IN LUMENS	max.3200
LUMEN PER WATT	89
POWER CONSUMPTION IN WATTS	36

Dimensions

diameter: 490mm
height: 115mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP44
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	IK07
LUMEN PER WATT	89
SUITED FOR EMERGENCY LIGHTING	No
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	0
ASSORTMENT	Proline
ETIM GRUPPEN-ID	EC002892
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No

DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IK07
SUITABLE FOR EMERGENCY LIGHTING	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No