

PRODUCT NO. 4485-1FW120-B-Ware

**DOTLUX LED surface mounted luminaire SURFACEsensor Ø300x62 25W 3000/4000/5700K
COLORselect white**



to the product page

- Version with motion (radar) and daylight sensor (several luminaires can be programmed with one remote control, please order remote control separately).
- Quick and easy mounting with EASYbase base plate and twistlock fastener
- Large product variety enables use in all projects (e.g. sensor, Exit, DALI ...)
- Sustainable design, LED module, power supply unit and battery can be replaced without tools
- Rear and side cable entry with large cable storage space allow flexible use on site
- Ideal for residential projects due to impact-resistant polycarbonate housing IK10
- Modern, clear housing with indirect light component
- Splash-proof design for outdoor, wet room and indoor use
- Individual light colour adjustable with COLORselect (light colour: 3,000 K / 4,000 K / 5,700 K)
- Suitable for central battery
- The large luminous surface made of polycarbonate creates a uniform and at the same time ceiling-brightening light distribution
- Flexible cable entry possible at the back and side

WEIGHT IN KG	1.1
LUMEN PER WATT	max.100
POWER CONSUMPTION IN WATTS	25
NET LUMINOUS FLUX IN LUMENS	2250-2500

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP54
LIGHT COLOR	multicoloured
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
IK PROTECTION	IK10
LUMEN PER WATT	max.100
PROTECTION CLASS	II
VOLTAGE TYPE	AC
HOUSING COLOUR	white
WARRANTY IN YEARS	0
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002892
IMPACT STRENGTH	IK10

Dimensions

height: 62mm
diameter: 300mm