

PRODUCT NO. 5825-040120

DOTLUX LED module QUICK-FIXdc 1430mm max.39W 1400mA (26-28V DC) 4000K



to the product page

- Universal magnetic LED light module for professional replacement of T5 & T8 fluorescent tubes
- Highly efficient 200 Watt LED board with lowest current consumption enables a system efficiency of 200 Lm/Watt
- Glare-free polycarbonate cover with 120° beam angle
- Tool-free replacement of the LED module also possible by a non-specialist thanks to DC system plug
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- 3 magnets and 75 cm long connection cable included in the scope of delivery
- Magnetic holders allow, among other things, direct screwing to the existing luminaire housing

The properties of the power supply unit also influence the properties of the luminaire system, e.g. dimmable, suitable for central battery, flicker-free, etc.

Recommended ballast not dimmable 100,000 hours Article number: 5043

Power consumption and net luminous flux of the module with different operating currents:

- 39W@ 1400mA = 6700lm = 172 lm/W
- 33W@ 1200mA = 5850lm = 177 lm/W
- 29W@ 1050mA = 5200lm = 179 lm/W
- 25W@ 900mA = 4500lm = 180 lm/W
- 22W@ 800mA = 4000lm = 182 lm/W
- 19W@ 700mA = 3500lm = 184 lm/W
- 14W@ 500mA = 2630lm = 188 lm/W
- 9W@ 350mA = 1800lm = 200 lm/W

ENERGY

DOTLUX
5825-040120

39
kWh/1000h

| | | | |
|------------------------------------|---|--------------------------------------|-----------|
| SUCCESSION ARTICLE | - | BEAM ANGLE | 120 |
| WEIGHT IN KG | 0.12 | PROTECTION CLASS (IP) | IP20 |
| POWER CONSUMPTION IN WATTS | 9/14/19/22/25/29/33/39 | Service life | |
| NET LUMINOUS FLUX IN LUMENS | 1800/2630/3500/4000/4500/5200/5850/6700 | COLOR TEMPERATURE IN KELVIN | 4000 |
| LUMEN PER WATT | max.200 | POWER FACTOR | 0,9 |
| | | LUMEN PER WATT | max.200 |
| | | PROTECTION CLASS | II |
| | | VOLTAGE TYPE | DC |
| Dimensions | | SWITCH CYCLES | > 200.000 |
| length: 1430mm | | INPUT VOLTAGE SPAN | 26-28 |
| width: 20mm | | WARRANTY IN YEARS | 5 |
| height: 17mm | | L80/B10 | 99999,8 |
| | | DIMMING WITHOUT DIMMER | No |
| | | INPUT VOLTAGE RANGE LUMINAIRE | 26-28 |
| | | ASSORTMENT | Proline |

| | |
|---|------------------------------------|
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | B |
| LIFETIME L80/B10 AT 25°C | 99999,8 |
| ETIM GRUPPEN-ID | ECC000996 |
| NO DIM FUNCTION | No |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| CONNECTION TYPE | Cable |
| PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 | RG1 |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | No |
| FLEXIBLE | Nein |
| SUITABLE FOR TRAFFIC LIGHTS | No |
| EXTERNAL DRIVER REQUIRED | Yes |
| SUITABLE FOR CONSTANT VOLTAGE | No |
| SUITABLE FOR GENERAL LIGHTING | Yes |
| SUITABLE FOR CONSTANT CURRENT | Yes |
| SUITABLE FOR RAIL TRAFFIC | No |
| SUITABLE FOR MATRIX INFORMATION BOARDS | No |
| SUITABLE FOR VARIABLE ROAD SIGNS | No |
| LIGHT COLOUR ACCORDING TO EN 12464-1 | neutral white 3300 to 5300 K |
| BEG FUNDING | Only relevant in Germany |
| LED-BETRIEBSSTROM IN MA | 350/500/700/800/900/1050/1200/1400 |
| SHAPE | Rectangular |
| COLOUR | White |