

PRODUCT NO. 4311-030120-B-Ware

DOTLUX LED spotlight FLOORslim-sensor 50W 3000K with motion detector PIR













to the product page

- Waterproof reinforced housing IP 65 with efficient cooling design.
- ESG safety glass -ULTRA CLEAR- highly transparent glass for excellent light Color and improved light output
- Rugged, thick-walled die-cast aluminum housing screwed together multiple times
- Mounting bracket freely rotatable (320°)
- Incl. 1 m connection cable (open ends HO5RN-F)
- At the swiveling sensor, the following values can be adjusted in steps:
 - o Range (up to 8 m)
 - o Daylight sensor
 - o Light Duration

SUCCESSION ARTICLE PREDECESSOR ARTICLE	5149-030120 2821-140120
WEIGHT IN KG POWER CONSUMPTION IN WATTS NET LUMINOUS FLUX IN LUMENS LUMEN PER WATT	2.45 50 5100 102

Dimensions

length: 312mm width: 279mm height: 46mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP65

INPUT VOLTAGE 100 - 240 V AC

SERVICE LIFE approx. 35.000 h at 25°C

COLOR TEMPERATURE IN KELVIN 3000
COLOR-RENDERING-INDEX CRI > 80

MOTION SENSOR Infrared on/off, 8m

INRUSH CURRENT IN A

IK PROTECTION

LUMEN PER WATT

PROTECTION CLASS

VOLTAGE TYPE

HOUSING COLOUR

SWITCH CYCLES

WARRANTY IN YEARS

O

IKO7

102

PROTECTION CLASS

I White

> 100.000

ENERGY EFFICIENCY CLASS

ACCORDING TO EU REGULATION not required

2019/2015

ETIM GRUPPEN-ID EC001744 DIMMING 0-10 V No DIMMING 1-10 V No **DIMMING DALI** No DIMMING DMX No **DIMMING DSI** No **DIMMING POTENTIOMETER** No (INTEGRATED) **DIMMING LINESWITCH** No



DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
IMPACT STRENGTH	IKO7
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0