

PRODUCT NO. 2354-335120-B-Ware

**DOTLUX LED moisture-proof luminaire MISTRAL IP66 640mm 26W 4000K frosted**



to the product page

<b>PREDECESSOR ARTICLE</b>	2354-240180	<b>BEAM ANGLE</b>	120
<b>WEIGHT IN KG</b>	1.084	<b>PROTECTION CLASS (IP)</b>	IP66
<b>POWER CONSUMPTION IN WATTS</b>	26	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>NET LUMINOUS FLUX IN LUMENS</b>	3500	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>LUMEN PER WATT</b>	135	<b>COLOR TEMPERATURE IN KELVIN</b>	4000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,9
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK08
<b>Dimensions</b>		<b>LUMEN PER WATT</b>	135
<b>length:</b> 640mm		<b>PROTECTION CLASS</b>	I
<b>width:</b> 100mm		<b>HOUSING COLOUR</b>	gray
<b>height:</b> 80mm		<b>SWITCH CYCLES</b>	> 100.000
		<b>FOOD-READY</b>	Yes
		<b>WARRANTY IN YEARS</b>	0
		<b>ASSORTMENT</b>	Proline
		<b>ETIM GRUPPEN-ID</b>	EC002892
		<b>DIMMING 0-10 V</b>	No
		<b>DIMMING 1-10 V</b>	No
		<b>DIMMING DALI</b>	No
		<b>DIMMING DMX</b>	No
		<b>DIMMING DSI</b>	No
		<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
		<b>DIMMING LINESWITCH</b>	No
		<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No

<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>IMPACT STRENGTH</b>	IK08
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0