

PRODUCT NO. 5893-099105

DOTLUX Surface-mounted LED light SOFTEDGE 23W/29W/35W/40W COLORselect POWERselect IP44 1200mm



to the product page

- Professional wall and ceiling light with large illuminated surface creates a uniform and ceiling-brightening light distribution
- Color-stable and glare-free thanks to prismatic, non-yellowing PMMA diffuser (IK07)
- One luminaire for all performance requirements: POWERSELECT in 4 levels (23W /29W /35W /40W)
- Simply set your favorite color yourself: DOTLUX COLORselect makes it easy to choose between different light colors (3000K/ 4000K/ 6000K)
- Tool-free quick-connect terminal (through-wirable with integrated strain relief)
- Flexible cable entry possible at the back and front
- Simple, flexible installation with 4 different mounting options
- Suitable for central battery

SUCCESSION ARTICLE	-	BEAM ANGLE	105
WEIGHT IN KG	2.151	PROTECTION CLASS (IP)	IP44
POWER CONSUMPTION IN WATTS	23 / 29 / 35 / 40	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	3220 - 5600	INPUT VOLTAGE	186 - 240 AC/DC
LUMEN PER WATT	140	Service life	
		COLOR TEMPERATURE IN KELVIN	3000/4000/6000
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,9
Dimensions		INRUSH CURRENT IN A	0
length: 1195mm		IK PROTECTION	IK07
width: 150mm		LUMEN PER WATT	140
height: 52mm		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	yes
		GLARE-FREE	UGR < 22
		SWITCH CYCLES	> 200.000
		INPUT VOLTAGE SPAN	180-264
		WARRANTY IN YEARS	5
		L80/B10	100000
		RATED CURRENT	0.11
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		INPUT VOLTAGE RANGE LUMINAIRE	180-264
		ASSORTMENT	Proline

ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LIFETIME L80/B10 AT 25°C	100000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	150000
ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR LIGHT LINE CONFIGURATION	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
SUITABLE FOR NUMBER OF LIGHT SOURCES	1
LAMP HOLDER	other Without
MATERIAL COVER	Plastic matt/satinized
TYPE OF CONTROL GEAR	LED operating device voltage-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM3
DEGREE OF PROTECTION (NEMA)	2
IMPACT STRENGTH	IK07
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	Yes
SUITABLE FOR EMERGENCY LIGHTING WITH MOVEMENT SENSOR	Yes
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	650 °C - 30 s
CONSTANT LIGHT OUTPUT (CLO)	No
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG0

COLOUR OF LIGHT ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	23 / 29 / 35 / 40
LAMP TYPE	LED exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	150000
LIFETIME L90/B10 AT 25°C	50000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	C
LIGHT OUTLET	Direct
TYPE OF WIRING	Suitable for through wiring
LUMINOUS FLUX ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
LIGHT SHARING	Symmetric
SURFACE PROTECTION HOUSING	Powder coating
TYPE OF GRID	None
LIGHT DISTRIBUTOR	None
BEAM ANGLE	Extreme wide beam >80°
CONNECTION TYPE	Other