

PRODUCT NO. 5896

DOTLUX Replacement power supply unit for LINEAtrack LED light insert













to the product page



SUCCESSION ARTICLE

WEIGHT IN KG 0.07
POWER CONSUMPTION IN WATTS 39-65

Dimensions

length: 260mm width: 25mm height: 15mm PROTECTION CLASS (IP) IP20

INPUT VOLTAGE 220 - 240 V AC

Service life

OUTPUT CURRENT IN A220-240POWER FACTOR0,9INRUSH CURRENT IN A30PROTECTION CLASSI

SWITCH CYCLES > 100.000 **OUTPUT VOLTAGE** 65-160 WARRANTY IN YEARS DIMMING WITHOUT DIMMER Nο ASSORTMENT Proline **ETIM GRUPPEN-ID** EC002710 DIMMING 0-10 V No DIMMING 1-10 V No **DIMMING DALI** Nο DIMMING DMX No DIMMING DSI No **DIMMING POTENTIOMETER** Nο (INTEGRATED) DIMMING LINESWITCH No **DIMMING MANUFACTURER'S** No PROPRIETARY SYSTEM

DIMMING MAINS VOLTAGE MODULATION NO DIMMING PHASE CUT-OFF NO DIMMING PROGRAMMABLE NO



DIMMING RF No DIMMING SINE WAVE REDUCTION No DIMMING TOUCH AND DIM No DIMMING ZIGBEE No DIMMING WITH PUSH-BUTTON No NO DIM FUNCTION Yes **CONSTANT LIGHT OUTPUT (CLO)** No **COMPATIBLE WITH CASAMBI** No **COMPATIBLE WITH APPLE HOMEKIT** No **COMPATIBLE WITH GOOGLE** No **ASSISTANT COMPATIBLE WITH AMAZON ALEXA** No IFTTT SUPPORT AVAILABLE No MODEL statisch SUITABLE FOR CONSTANT VOLTAGE No SUITABLE FOR OUTDOOR USE No SUITABLE FOR DC-VOLTAGE (PRIMARY No SIDE) SUITABLE FOR CONSTANT CURRENT HOUSING **DIMMING PHASE CUT-ON** No DIMMING GPRS No PULSE DURATION IN µS **BEG FUNDING** Only relevant in Germany