

PRODUCT NO. 5991-030030

**DOTLUX Wall light Sixfold 6W 3000K black**



to the product page

- Equipped outdoor wall light with 6 light outlets (3 at the top and 3 at the bottom) to create an impressive play of light. With its asymmetrical lens, it provides particularly uniform and targeted illumination.
- The DOTLUX Sixfold is ideal for accent lighting and creates a pleasant atmosphere.
- The aluminum housing is not only robust, but also aesthetically pleasing. Whether you install it on the patio or at the front door, it will instantly enhance your outdoor area.
- Anti-glare lens cover reduces light pollution
- Double sealing grommets for through-wiring
- Robust splash-proof housing
- Direct wall mounting indoors and outdoors
- Housing color similar to RAL 9005

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	30x20
<b>WEIGHT IN KG</b>	0.42	<b>PROTECTION CLASS (IP)</b>	IP65
<b>LUMEN PER WATT</b>	53	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	6	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>NET LUMINOUS FLUX IN LUMENS</b>	320	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,8
		<b>IK PROTECTION</b>	IK06
<b>Dimensions</b>		<b>LUMEN PER WATT</b>	53
<b>width:</b> 94mm		<b>PROTECTION CLASS</b>	I
<b>height:</b> 49mm		<b>VOLTAGE TYPE</b>	AC
<b>length:</b> 165mm		<b>HOUSING COLOUR</b>	black
		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	60000
		<b>SIMILAR TO RAL-COLOUR</b>	9005
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>MOUNTING LOCATION</b>	Indoor + covered outdoor
		<b>LIFETIME L80/B10 AT 25°C</b>	60000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	90000
		<b>ETIM GRUPPEN-ID</b>	EC002892

<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	No
<b>SUITABLE FOR LIGHT LINE CONFIGURATION</b>	No
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>MATERIAL COVER</b>	Plastic, structured
<b>WITH CONTROL GEAR</b>	Yes
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	No
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>LIGHT DISTRIBUTOR</b>	Focal lens
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK06
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	No
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>WITH AIR SLOTS</b>	No
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	-
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No

<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	90000
<b>LIFETIME L90/B10 AT 25°C</b>	30000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE</b>	F
<b>LIGHT SHARING</b>	Asymmetric
<b>TYPE OF WIRING</b>	Suitable for through wiring
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT OUTLET</b>	Direct/indirect
<b>BEAM ANGLE</b>	Medium beam 21-40°
<b>SURFACE PROTECTION HOUSING</b>	Other
<b>TYPE OF CONTROL GEAR</b>	Not required
<b>DEGREE OF PROTECTION (NEMA)</b>	Other