

PRODUCT NO. 5992-030030

**DOTLUX Wall light Sixfold 6W 3000K white**



to the product page

This DOTLUX outdoor wall light is equipped with 6 light outlets (3 at the top and 3 at the bottom) to create an impressive play of light. With its asymmetrical lens, it provides particularly uniform and targeted illumination.

The DOTLUX Sixfold is ideal for accent lighting and creates a pleasant atmosphere.

The aluminum housing is not only robust, but also aesthetically pleasing. Whether you install it on the patio or at the front door, it will immediately enhance your outdoor area.

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	30x20
<b>WEIGHT IN KG</b>	0.42	<b>PROTECTION CLASS (IP)</b>	IP65
<b>POWER CONSUMPTION IN WATTS</b>	6	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	320	<b>INPUT VOLTAGE</b>	220 - 240 V AC
<b>LUMEN PER WATT</b>	53	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
		<b>COLOR TEMPERATURE IN KELVIN</b>	3000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,8
		<b>IK PROTECTION</b>	IK06
		<b>LUMEN PER WATT</b>	53
		<b>PROTECTION CLASS</b>	I
		<b>VOLTAGE TYPE</b>	AC
		<b>HOUSING COLOUR</b>	white
		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	60000
		<b>SIMILAR TO RAL-COLOUR</b>	9005
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>MOUNTING LOCATION</b>	Indoor + covered outdoor
		<b>LIFETIME L80/B10 AT 25°C</b>	60000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	90000
		<b>ETIM GRUPPEN-ID</b>	EC002892

**Dimensions**

**length:** 165mm

**width:** 94mm

**height:** 51mm

<b>WITH ILLUMINANT</b>	Yes
<b>SUITABLE FOR WALL MOUNTING</b>	Yes
<b>SUITABLE FOR SUSPENDED MOUNTING</b>	No
<b>SUITABLE FOR CEILING MOUNTING</b>	No
<b>SUITABLE FOR LIGHT LINE CONFIGURATION</b>	No
<b>SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1</b>	No
<b>MATERIAL COVER</b>	Plastic, structured
<b>WITH CONTROL GEAR</b>	No
<b>DIMMING 0-10 V</b>	No
<b>DIMMING 1-10 V</b>	No
<b>DIMMING DALI</b>	No
<b>DIMMING DMX</b>	Yes
<b>DIMMING DSI</b>	No
<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
<b>DIMMING LINESWITCH</b>	No
<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	Yes
<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	No
<b>LIGHT DISTRIBUTOR</b>	Focal lens
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6
<b>IMPACT STRENGTH</b>	IK06
<b>LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24</b>	No
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	No
<b>WITH MOVEMENT SENSOR</b>	No
<b>WITH LIGHT SENSOR</b>	No
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>WITH AIR SLOTS</b>	No
<b>FILAMENT TEST ACCORDING TO IEC 60695-2-11</b>	750 °C - 30 s
<b>OPERATION BY BLUETOOTH</b>	No
<b>COMPATIBLE WITH CASAMBI</b>	No
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No
<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>DIMMING DALI-2</b>	No

<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	90000
<b>LIFETIME L90/B10 AT 25°C</b>	30000
<b>BEG FUNDING</b>	Only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE</b>	F
<b>LIGHT SHARING</b>	Asymmetric
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT OUTLET</b>	Direct/indirect
<b>BEAM ANGLE</b>	Medium beam 21-40°
<b>SURFACE PROTECTION HOUSING</b>	Other
<b>TYPE OF CONTROL GEAR</b>	Not required
<b>DEGREE OF PROTECTION (NEMA)</b>	Other