

PRODUCT NO. 5997-030110

DOTLUX LED indoor wall light FLAME 8W 3000K white



to the product page

- Modern, decorative wall light with direct and indirect lighting
- Unique design with great decorative effect
- Excellent heat management thanks to aluminum housing ensures a long service life
- Housing color similar to RAL 9016

SUCCESSION ARTICLE	-	BEAM ANGLE	110
WEIGHT IN KG	0.551	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	8	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	632	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	79	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	3000
		COLOR-RENDERING-INDEX	CRI > 80
		POWER FACTOR	0,88
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK00
		LUMEN PER WATT	79
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC
		HOUSING COLOUR	white
		SUITED FOR EMERGENCY LIGHTING	No
		WARRANTY IN YEARS	3
		L80/B10	54000
		SIMILAR TO RAL-COLOUR	9006
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		MOUNTING LOCATION	Indoor
		LIFETIME L80/B10 AT 25°C	54000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	81000
		ETIM GRUPPEN-ID	EC002892

Dimensions

length: 120mm

width: 140mm

height: 70mm

SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	No
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
MATERIAL COVER	Plastic matt/satinized
WITH CONTROL GEAR	No
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	Yes
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
IMPACT STRENGTH	IK00
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
WITH AIR SLOTS	No
FILAMENT TEST ACCORDING TO IEC 60695-2-11	750 °C - 30 s
TYPE OF WIRING	Ending
LUMINOUS FLUX ADJUSTABLE	Positions
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
SUITABLE FOR LAMP POWER IN W	8
LAMP TYPE	LED not exchangeable
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
LIFETIME L70/B50 AT 25°C	81000

LIFETIME L90/B10 AT 25°C	27000
PULSE DURATION IN µS	0
BEG FUNDING	Only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHE	F
LIGHT SHARING	Asymmetric
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No
TYPE OF GRID	Matt
LIGHT OUTLET	Direct/indirect
SURFACE PROTECTION HOUSING	Plastic-coated
LIGHT DISTRIBUTOR	Other
BEAM ANGLE	Extreme wide beam >80°
CONNECTION TYPE	Other