

PRODUCT NO. 4556-140140

DOTLUX LED EX safety light MISTRALex EX Protected IP66 1572mm 53W 4000K IK10 Zone 2 & 22



to the product page

- UV-stable, shatterproof IK10/IP66 polycarbonate housing with frosted cover ensures shadow-free light distribution
- Stainless steel catches with integrated anti-theft device
- Can be wired through with an internal 3-pole luminaire connection terminal
- Now supplied with two ATEX cable glands (incl. one dummy plug)
- Silicone-free, also for paint shops
- Suitable for central battery
- ATEX certified
- Explosion group:
 - II 3 G Ex ec IIC T6 Gc
 - II 3 D Ex tc IIIC T85°C Dc IP66
- The D mark of this luminaire with limited surface temperature is a basic requirement for luminaires in flammable locations (DIN EN 60598-2-24, VDE 0711-2-24)
- Sustainable product design thanks to easily replaceable components

SUCCESSION ARTICLE	-	BEAM ANGLE	140
PREDECESSOR ARTICLE	4556-040140	PROTECTION CLASS (IP)	IP66
WEIGHT IN KG	3.7	LIGHT COLOR	white
POWER CONSUMPTION IN WATTS	53	INPUT VOLTAGE	176 - 240 V AC/DC
NET LUMINOUS FLUX IN LUMENS	8300	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	156	COLOR TEMPERATURE IN KELVIN	4000
		POWER FACTOR	0,98
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK10
		LUMEN PER WATT	156
		PROTECTION CLASS	I
		VOLTAGE TYPE	AC/DC
		WARRANTY IN YEARS	7
		L80/B10	50000
		DIMMING WITHOUT DIMMER	No
		ASSORTMENT	Highline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	50000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
		ETIM GRUPPEN-ID	EC001952
		WITH ILLUMINANT	Yes
		LAMP HOLDER	-
		MATERIAL COVER	Plastic matt/satinized
		WITH CONTROL GEAR	Yes
		LIGHT DISTRIBUTOR	Diffuser lens/optic/panel
Dimensions			
length:	1572mm		
width:	145mm		
height:	111mm		

IMPACT STRENGTH	IK10
CONSTANT LIGHT OUTPUT (CLO)	No
CONNECTION TYPE	Push-in clamp
ADJUSTABLE	Nein
LAMP TYPE	LED exchangeable
MOUNTING METHOD	Wall/ceiling mounting
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
TYPE OF WIRING	Suitable for through wiring
BEAM ANGLE	Extreme wide beam >80°