


PRODUCT NO. 4446-0FW120-B-Ware

DOTLUX LED-Downlight UNISIZEplus 12W COLORselect



to the product page

- Dimmable recessed luminaire for all recessed openings from 60-130mm (phase cut-off)
- Easy mounting thanks to removable, infinitely adjustable mounting bracket with safety catch/mounting aid
- Removable spring clips allow direct screw mounting to wall and ceiling
- Extremely space-saving design due to integrated control gear
- Stable light output due to non-yellowing PMMA light guide
- Decorative rings in 3 colors with magnetic attachment optionally available
- Can also be integrated into DALI networks via optional DALI phase cut-off dimmer
- COLORselect: 3 light colors in one luminaire. The right light color for every application:
 - Warm white 3,000K: Hotel, store, wellness/spa areas, home & living.
 - Neutral white 4.000K: Office, gastronomy, sanitary, senior citizen and hospitals
 - Daylight white 5,700K: conference rooms, educational institutions, office

WEIGHT IN KG	0.28
POWER CONSUMPTION IN WATTS	10,76W
NET LUMINOUS FLUX IN LUMENS	960
LUMEN PER WATT	80

Dimensions

height: 15mm
diameter: 164mm

BEAM ANGLE	120
PROTECTION CLASS (IP)	IP20
LIGHT COLOR	multicoloured
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 35.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	3000/4000/5700
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,9
INRUSH CURRENT IN A	0
LUMEN PER WATT	80
PROTECTION CLASS	II
GLARE-FREE	UGR < 25
SWITCH CYCLES	> 70.000
INSTALLATION OPENING DIAMETER IN MM	60-130
WARRANTY IN YEARS	0
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	35000
ETIM GRUPPEN-ID	EC001744
SUITABLE FOR WALL MOUNTING	No
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
COMPATIBLE WITH APPLE HOMEKIT	No

COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
EXCHANGEABLE CONTROL GEAR	No
EMERGENCY POWER SUPPLY INTEGRATED	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	Yes
LIFETIME L70/B50 AT 25°C	35000
PULSE DURATION IN µS	0
BEAM ANGLE ADJUSTABLE	No