

PRODUCT NO. 4865-150060

**DOTLUX LED floodlight LENSplus 100W 5000K 60° beam angle**



to the product page

Large variety of different beam angles enables optimum illumination for every situation

- Reliable operation thanks to highly efficient Lumileds® LEDs with 3-step MacAdam binning
- Solid, waterproof, ADC12 die-cast aluminum housing with pressure equalization valve (IP 66/IK08) and high-quality powder coating from Akzo Nobel
- ESG glass "ULTRA CLEAR" highly transparent glass for excellent light color and improved light output
- Durable industrial power supply units with 10kV overvoltage protection
- Curved mounting bracket enables easy installation without having to dismantle the bracket (freely rotatable 320°)
- Easy installation thanks to cable connector
- Replaceable components therefore repairable
- Sustainable product design thanks to easily replaceable components

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	60
<b>PREDECESSOR ARTICLE</b>	3017-155060K	<b>PROTECTION CLASS (IP)</b>	IP66
<b>WEIGHT IN KG</b>	3.238	<b>LIGHT COLOR</b>	white
<b>POWER CONSUMPTION IN WATTS</b>	100	<b>INPUT VOLTAGE</b>	176 - 240 V AC/DC
<b>NET LUMINOUS FLUX IN LUMENS</b>	14700	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>LUMEN PER WATT</b>	147	<b>COLOR TEMPERATURE IN KELVIN</b>	5000
		<b>COLOR-RENDERING-INDEX</b>	CRI > 82
		<b>POWER FACTOR</b>	0,98
		<b>INRUSH CURRENT IN A</b>	0
		<b>IK PROTECTION</b>	IK08
		<b>LUMEN PER WATT</b>	147
		<b>PROTECTION CLASS</b>	I
		<b>VOLTAGE TYPE</b>	AC/DC
		<b>HOUSING COLOUR</b>	black
		<b>SUITED FOR EMERGENCY LIGHTING</b>	No
		<b>SWITCH CYCLES</b>	> 100.000
		<b>OVERVOLTAGE PROTECTION</b>	up to 10000 V
		<b>WARRANTY IN YEARS</b>	7
		<b>L80/B10</b>	50000
		<b>SUITABLE FOR SURFACE MOUNTING</b>	Yes
		<b>SUITABLE FOR MOUNTING</b>	No
		<b>DIMMING WITHOUT DIMMER</b>	No
		<b>ENABLED LICENSED PRODUCT</b>	Yes
		<b>ASSORTMENT</b>	Highline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
<b>Dimensions</b>			
<b>length:</b>	375mm		
<b>width:</b>	288mm		
<b>height:</b>	72mm		

LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC001744
WITH ILLUMINANT	Yes
SUITABLE FOR WALL MOUNTING	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	Yes
SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1	No
LAMP HOLDER	-
MATERIAL COVER	Glass transparent
TYPE OF CONTROL GEAR	LED operating device current-controlled
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	No
LIGHT DISTRIBUTOR	Focal lens
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK08
SUITABLE FOR EMERGENCY LIGHTING	No
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE	No
TYPE OF WIRING	Ending
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR LOW VOLTAGE CABLE SYSTEM	No
SUITABLE FOR CLAMP-MOUNTING	Yes
SUITABLE FOR LIGHT-TRACK MOUNTING	No

<b>SUITABLE FOR PEDESTAL/FLOOR MOUNTING</b>	Yes
<b>SUITABLE FOR TRAVERSE MOUNTING</b>	Yes
<b>EXCHANGEABLE CONTROL GEAR</b>	No
<b>LAMP TYPE</b>	LED not exchangeable
<b>EMERGENCY POWER SUPPLY INTEGRATED</b>	No
<b>SURFACE BRUSHED</b>	No
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	only relevant in Germany
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	D
<b>LIGHT OUTLET</b>	Direct
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>LUMINOUS FLUX ADJUSTABLE</b>	No
<b>BEAM ANGLE ADJUSTABLE</b>	No
<b>LIGHT SHARING</b>	Symmetric
<b>ADJUSTABILITY</b>	Swivelling
<b>SURFACE PROTECTION</b>	Powder coating
<b>BEAM ANGLE</b>	Wide beam 41-80°
<b>CONNECTION TYPE</b>	Other