

PRODUCT NO. 5124-1

CASAMBI Gateway for up to 2 networks



to the product page

- Hardware gateway for convenient operation of up to 2 Casambi networks
- Programming of the gateway and sites functionality in the Casambi app
- Remote access via Ethernet or WIFI
- The gateway can be used for remote diagnostics, network monitoring or remote control
- Range max. 30m in free field
- HDMI cable and power supply included in the scope of delivery
- USB mouse for easy commissioning
- External LTE antenna

SUCCESSION ARTICLE -
PREDECESSOR ARTICLE ohne 5.Ghz

WEIGHT IN KG 0.52

Dimensions

length: 108mm

width: 104mm

height: 28mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
VOLTAGE TYPE	AC
INPUT VOLTAGE SPAN	100-240
INPUT VOLTAGE RANGE LUMINAIRE	100-240
ETIM GRUPPEN-ID	ECC001099
MODEL	Multiple interfaces
BUS SYSTEM RADIO BUS	No
BUS SYSTEM KNX	No
BUS SYSTEM KNX-RF (FUNK)	No
BUS SYSTEM LON	No
BUS SYSTEM POWERNET	No
BEG FUNDING	Only relevant in Germany
MOUNTING METHOD	Other