

PRODUCT NO. 6161-040170

DOTLUX QUICK-FIXadapt 29W 4000K interchangeable module




to the product page

- Universal LED light module for quick and easy replacement of all conventional light sources in ceiling and wall luminaires
- Tool-free replacement of the LED module even by a non-specialist thanks to DC system plug
- Special lenses with 170° beam angle of the LED module also possible by a non-specialist
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- the QUICKFIX-adapt can be set up to 700mA with the matching 5068-1 power supply unit.
- inner diameter 25cm
- Outer diameter 30cm

Power consumption and net luminous flux of the module with different operating currents:

- 12W@ 300mA = 2220lm = 185lm/W
- 14W@ 350mA = 2570lm = 184lm/W
- 16W@ 400mA = 2925lm = 183lm/W
- 18W@ 450mA = 3290lm = 183lm/W
- 23W@ 550mA = 3930lm = 171lm/W
- 25W@ 600mA = 4140lm = 166lm/W
- 27W@ 650mA = 4600lm = 170lm/W
- 29W@ 700mA = 4850lm = 167lm/W



SUCCESSION ARTICLE	-	BEAM ANGLE	170
WEIGHT IN KG	0.107	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	29	SERVICE LIFE	approx. 50.000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	4850	COLOR TEMPERATURE IN KELVIN	4000
LUMEN PER WATT	167	POWER FACTOR	0,9
		LUMEN PER WATT	167
		PROTECTION CLASS	-
		VOLTAGE TYPE	DC
		SWITCH CYCLES	> 100.000
Dimensions		INPUT VOLTAGE SPAN	40-43
height: 20mm		WARRANTY IN YEARS	3
diameter: 300mm		L80/B10	50000
		DIMMING WITHOUT DIMMER	No
		ENABLED LICENSED PRODUCT	Yes
		INPUT VOLTAGE RANGE LUMINAIRE	40-43
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
		LIFETIME L80/B10 AT 25°C	50000
		ETIM GRUPPEN-ID	EC000996

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM4
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
FLEXIBLE	Nein
SUITABLE FOR TRAFFIC LIGHTS	No
EXTERNAL DRIVER REQUIRED	Yes
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIGHT COLOUR ACCORDING TO EN 12464-1	neutral white 3300 to 5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	700
SHAPE	Round
COLOUR	White