

PRODUCT NO. 4774-040050-B-Ware

DOTLUX LED damp-proof luminaire HIGHFORCEnarrow IP66/IP69 1455mm 54W 4000K IK06 1x3-pole



to the product page

- UV-stable diffuser and housing
- Chemical resistant special diffuser made of ChemRST material
- Suitable for agricultural operations
- Housing made of impact-resistant polycarbonate
- IK06 impact resistance
- Suitable for central battery
- IP66/ IP69
- D-certified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- Suitable for mounting heights from 6m thanks to narrow beam optics
- All HIGHFORCE luminaires are supplied without connector plug. You can find accessories here in the shop.

WEIGHT IN KG	1.7
POWER CONSUMPTION IN WATTS	54
NET LUMINOUS FLUX IN LUMENS	6960
LUMEN PER WATT	129

Dimensions

length: 1455mm
width: 90mm
height: 99mm

BEAM ANGLE	50
PROTECTION CLASS (IP)	other IP66 / IP69
INPUT VOLTAGE	176 - 240 V AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
COLOR-RENDERING-INDEX	CRI > 82
POWER FACTOR	0,95
INRUSH CURRENT IN A	0
IK PROTECTION	IK06
LUMEN PER WATT	129
PROTECTION CLASS	I
HOUSING COLOUR	gray
FOOD-READY	Yes
WARRANTY IN YEARS	0
ASSORTMENT	Highline
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No

DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0