

PRODUCT NO. 4783-040120-B-Ware

DOTLUX LED damp-proof luminaire HIGHFORCEabs IP66/IP69 1455mm 27W 4000K IK06 2x5-pole through-wired DALI including end cap



to the product page

- UV-stable diffuser and housing
- Chemical resistant special diffuser made of ChemRST material
- Suitable for agricultural operations
- Housing made of impact-resistant polycarbonate
- IK06 impact resistance
- Suitable for central battery
- IP66 / IP69
- Decertified
- DLG certified
- Distance between both mounting brackets adjustable (700-980mm)
- Mounting brackets allow ceiling and/or wall mounting
- All HIGHFORCE lights are supplied without connector plug. You can find accessories here in the store.

| | | | |
|------------------------------------|-------------|--|--------------------------|
| SUCCESSION ARTICLE | 4783-140120 | BEAM ANGLE | 120 |
| WEIGHT IN KG | 1.8 | PROTECTION CLASS (IP) | other IP66 / IP69 |
| POWER CONSUMPTION IN WATTS | 27 | INPUT VOLTAGE | 176 - 240 V AC/DC |
| NET LUMINOUS FLUX IN LUMENS | 3570 | SERVICE LIFE | approx. 50.000 h at 25°C |
| LUMEN PER WATT | 132 | COLOR TEMPERATURE IN KELVIN | 4000 |
| | | COLOR-RENDERING-INDEX | CRI > 82 |
| | | POWER FACTOR | 0,95 |
| | | INRUSH CURRENT IN A | 0 |
| | | IK PROTECTION | IK06 |
| | | LUMEN PER WATT | 132 |
| | | PROTECTION CLASS | I |
| | | HOUSING COLOUR | gray |
| | | FOOD-READY | Yes |
| | | WARRANTY IN YEARS | 0 |
| | | ASSORTMENT | Highline |
| | | COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| | | IMPACT STRENGTH | IK06 |
| | | DIMMING DALI-2 | Yes |
| | | PULSE DURATION IN µS | 0 |
| Dimensions | | | |
| length: | 1455mm | | |
| width: | 90mm | | |
| height: | 96mm | | |