


PRODUCT NO. 3138-1-M

LED power supply QUICK-FIXadapt CC 13-30W 500-700mA 26-42V dimmable phase cut-off/cut-on



to the product page

- For QUICK-FIXadapt incl. magnetic attachment
- The power supply unit is dimmable via trailing-edge phase-cut dimmer or leading-edge phase-cut dimmer
- With constant current technology (CC), it is suitable for luminaires with constant current
- The connected constant current luminaires can be dimmed between 10%-100%
- Suitable dimmers: JUNG 1224 LED UDE, Eltako EUD61NPL-230V, GIRA Mini2440 00 and many more.
- The output current is adjustable: 500/550/600/700mA
- The power supply unit is set to 500mA as standard

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	4937
WEIGHT IN KG	0.153
POWER CONSUMPTION IN WATTS	13-30

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
OUTPUT CURRENT IN A	0,5-0,7
INRUSH CURRENT IN A	0
TC TEMPERATURE IN °C	85
PROTECTION CLASS	II
OVERVOLTAGE PROTECTION	1000 V
OUTPUT VOLTAGE	26 - 42 DC
INPUT VOLTAGE SPAN	198-264
WARRANTY IN YEARS	5
DIMMING WITHOUT DIMMER	No
INPUT VOLTAGE RANGE LUMINAIRE	198-264
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	Yes
DIMMING PHASE CUT-OFF	Yes
DIMMING PROGRAMMABLE	No
DIMMING RF	No

Dimensions

length: 138mm
width: 44mm
height: 44mm

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	No
CONSTANT LIGHT OUTPUT (CLO)	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
SUITABLE FOR OUTDOOR USE	Yes
SUITABLE FOR CONSTANT CURRENT HOUSING	Yes
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	Yes
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany