

PRODUCT NO. 3379-140170

DOTLUX QUICK-FIXplus 12W 4000K replaceable LED module



to the product page

- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 158lm/W thanks to low-current LEDs and therefore long service life
- Our QUICK-FIXplus luminaires have DIN EN60598-2-22:2014 certification, which confirms their approval for emergency lighting.
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 500 mm
- Suitable for central battery
- Tool-free replacement of the LED module even by a non-specialist thanks to AC system plug

SUCCESSION ARTICLE	-	BEAM ANGLE	170
PREDECESSOR ARTICLE	3379-040170	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.172	INPUT VOLTAGE	186 - 240 AC/DC
LUMEN PER WATT	158	SERVICE LIFE	approx. 50.000 h at 25°C
POWER CONSUMPTION IN WATTS	12	COLOR TEMPERATURE IN KELVIN	4000
NET LUMINOUS FLUX IN LUMENS	1900	POWER FACTOR	0,9
		Lumen per watt	
		PROTECTION CLASS	II
		VOLTAGE TYPE	AC/DC
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	3
		L80/B10	50000
		DIMMING WITHOUT DIMMER	No
		ENABLED LICENSED PRODUCT	Yes
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
		MOUNTING LOCATION	Indoor
		LIFETIME L80/B10 AT 25°C	50000
		LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
		ETIM GRUPPEN-ID	EC000996
		NO DIM FUNCTION	Yes
		COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM5
		CONNECTION TYPE	Cable

Dimensions

height: 40mm
diameter: 180mm

PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
FLEXIBLE	Nein
SUITABLE FOR TRAFFIC LIGHTS	No
EXTERNAL DRIVER REQUIRED	No
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIFETIME L70/B50 AT 25°C	100000
LIFETIME L90/B10 AT 25°C	25000
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	62
SHAPE	Round
COLOUR	White