

PRODUCT NO. 3670-399160-B-Ware

DOTLUX LED luminaire LUNAsilver Ø490mm 36W COLORselect IP44



to the product page

1. Decorative ring made of high quality brushed aluminum
2. Cozy atmosphere due to indirect light components
3. Shadow-free light distribution with very stable PMMA cover IK07
4. Constant light output due to large-area aluminum core board
5. Easy installation, thanks to through-wireable luminaire terminal block
6. Sustainable, repairable product design

PREDECESSOR ARTICLE	3670-1FW160 3670-2FW160	BEAM ANGLE	120
WEIGHT IN KG	1.47	PROTECTION CLASS (IP)	IP44
POWER CONSUMPTION IN WATTS	36	INPUT VOLTAGE	220 - 240 V AC
NET LUMINOUS FLUX IN LUMENS	max.3500	SERVICE LIFE	approx. 50.000 h at 25°C
LUMEN PER WATT	97	COLOR TEMPERATURE IN KELVIN	3000/4000/5700
		COLOR-RENDERING-INDEX	CRI > 82
		POWER FACTOR	0,96
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK07
Dimensions		LUMEN PER WATT	97
height: 115mm		SUITED FOR EMERGENCY LIGHTING	No
diameter: 490mm		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	0
		ASSORTMENT	Proline
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No

DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK07
SUITABLE FOR EMERGENCY LIGHTING	No
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany