

PRODUCT NO. 6355-12

LED power supply unit CV 12V/DC 20W 0-1.67A SELV IP20



to the product page



- Super-flat LED power supply unit
- Flicker-free design
- Output is SELV-compliant and protected against short circuit, overload and overheating.

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
PREDECESSOR ARTICLE	4249-12	INPUT VOLTAGE	220 - 240 V AC
WEIGHT IN KG	0.07	SERVICE LIFE	approx. 35.000 h at 25°C
POWER CONSUMPTION IN WATTS	20	OUTPUT CURRENT IN A	0-1,67
		POWER FACTOR	0,85
		INRUSH CURRENT IN A	30
		TC TEMPERATURE IN °C	85
		PROTECTION CLASS	II
Dimensions		OUTPUT VOLTAGE	12 DC
length: 121mm		INPUT VOLTAGE SPAN	198-264
width: 45mm		DIMMING WITHOUT DIMMER	No
height: 16mm		INPUT VOLTAGE RANGE LUMINAIRE	198-264
		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
CONSTANT LIGHT OUTPUT (CLO)	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
MODEL	statisch
SUITABLE FOR CONSTANT VOLTAGE	Yes
SUITABLE FOR OUTDOOR USE	No
SUITABLE FOR CONSTANT CURRENT	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	50
BEG FUNDING	Only relevant in Germany