

PRODUCT NO. 5830-50

DOTLUX LED module QUICK-FIXdc 820mm max.14W 500mA (25-28V DC) 5700K Set 50 pieces



to the product page

- Universal magnetic LED light module for the professional replacement of T5 & T8 fluorescent tubes
- Highly efficient 100 watt LED board with lowest current consumption enables a system efficiency of max. 198 Lm/watt
- Glare-free polycarbonate cover with 120° beam angle
- Tool-free replacement of the LED module also possible by a non-specialist thanks to DC system plug
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- 2 magnets and 50 cm long connection cable included in the scope of delivery
- Magnetic holders allow, among other things, a direct screw connection to the existing luminaire housing

The properties of the power supply unit also influence the properties of the luminaire system, e.g. dimmable, suitable for central battery, flicker-free, etc.

Recommended ballast not dimmable 100,000 hours Article number: 5136

Power consumption and net luminous flux of the module with different operating currents:

- 14W@ 500mA = 2510lm = 179lm/W
- 10W@ 350mA = 1800lm = 180lm/W
- 7W@ 250mA = 1300lm = 186lm/W
- 4W@ 150mA = 790lm = 198lm/W

SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	4	PROTECTION CLASS (IP)	IP20
NET LUMINOUS FLUX IN LUMENS	790/1300/1800/2510	SERVICE LIFE	approx. 200,000 h at 25°C
POWER CONSUMPTION IN WATTS	4/7/10/14	COLOR TEMPERATURE IN KELVIN	5700
LUMEN PER WATT	max.198	POWER FACTOR	0,9
		LUMEN PER WATT	max.198
		PROTECTION CLASS	II
		VOLTAGE TYPE	DC
		INPUT VOLTAGE SPAN	25-28
Dimensions		WARRANTY IN YEARS	5
width: 20mm		L80/B10	100000
height: 17mm		DIMMING WITHOUT DIMMER	No
length: 820mm		ENABLED LICENSED PRODUCT	Yes
		INPUT VOLTAGE RANGE LUMINAIRE	25-28
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	B
		LIFETIME L80/B10 AT 25°C	100000
		ETIM GRUPPEN-ID	EC000996

NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM1
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
FLEXIBLE	Nein
SUITABLE FOR TRAFFIC LIGHTS	No
EXTERNAL DRIVER REQUIRED	Yes
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	150/250/350/500
SHAPE	Rectangular
COLOUR	White