

PRODUCT NO. 5828-50

DOTLUX LED module QUICK-FIXdc 500mm max.15W 500mA (27-29V DC) 5700K Set 50 pieces



to the product page

- Universal magnetic LED light module for the professional replacement of T5 & T8 fluorescent tubes
- Highly efficient 70 watt LED circuit board with lowest current consumption enables a system efficiency of max. 186 Lm/watt
- Glare-free polycarbonate cover with 120° beam angle
- Tool-free replacement of the LED module also possible by a non-specialist thanks to DC system plug
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- 2 magnets and 50cm long connection cable included in the scope of delivery

The properties of the power supply unit also influence the properties of the luminaire system, e.g. dimmable, suitable for central battery, flicker-free, etc.

Recommended ballast not dimmable 100,000 hours Article number: 5136

Power consumption and net luminous flux of the module with different operating currents:

- 15W@ 500 mA = 2650lm = 177lm/W
- 10W@ 350 mA = 1850lm = 185lm/W
- 7W@ 250 mA = 1300lm = 186lm/W

SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	3	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	7/10/15	SERVICE LIFE	approx. 200,000 h at 25°C
NET LUMINOUS FLUX IN LUMENS	1300/1850/2650	COLOR TEMPERATURE IN KELVIN	5700
LUMEN PER WATT	max.186	POWER FACTOR	0,9
		LUMEN PER WATT	max.186
		PROTECTION CLASS	II
		VOLTAGE TYPE	DC
		INPUT VOLTAGE SPAN	27-29
		WARRANTY IN YEARS	5
		L80/B10	100000
		DIMMING WITHOUT DIMMER	No
		ENABLED LICENSED PRODUCT	Yes
		INPUT VOLTAGE RANGE LUMINAIRE	27-29
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	B
		LIFETIME L80/B10 AT 25°C	100000
		ETIM GRUPPEN-ID	EC000996
		NO DIM FUNCTION	No

Dimensions

length: 500mm
width: 20mm
height: 17mm

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM1
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
FLEXIBLE	Nein
SUITABLE FOR TRAFFIC LIGHTS	No
EXTERNAL DRIVER REQUIRED	Yes
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	250/350/500
SHAPE	Rectangular
COLOUR	White