

PRODUCT NO. 5834-50

DOTLUX LED module QUICK-FIXdc 1430mm max.39W 1400mA (26-28V DC) 5700K 50 pieces



to the product page

- Universal magnetic LED light module for the professional replacement of T5 & T8 fluorescent tubes
- Highly efficient 200 Watt LED board with lowest current consumption enables a system efficiency of 200 Lm/Watt
- Glare-free polycarbonate cover with 120° beam angle
- Tool-free replacement of the LED module also possible by a non-specialist thanks to DC system plug
- Full flexibility thanks to external power supply unit (power supply unit must be ordered separately)
- 3 magnets and 75cm long connection cable included in the scope of delivery

The properties of the power supply unit also influence the properties of the luminaire system, e.g. dimmable, suitable for central battery, flicker-free, etc.

Recommended ballast not dimmable 100,000 hours Article number: 5136

Power consumption and net luminous flux of the module with different operating currents:

- 39W@ 1400mA = 6700lm = 172 lm/W
- 33W@ 1200mA = 5850lm = 177 lm/W
- 29W@ 1050mA = 5200lm = 179 lm/W
- 25W@ 900mA = 4500lm = 180 lm/W
- 22W@ 800mA = 4000lm = 182 lm/W
- 19W@ 700mA = 3500lm = 184 lm/W
- 9W@ 350mA = 1800lm = 200 lm/W

SUCCESSION ARTICLE	-	BEAM ANGLE	120
WEIGHT IN KG	6.5	PROTECTION CLASS (IP)	IP20
LUMEN PER WATT	max.200	SERVICE LIFE	approx. 200,000 h at 25°C
POWER CONSUMPTION IN WATTS	9/14/19/22/25/29/33/39	COLOR TEMPERATURE IN KELVIN	5700
NET LUMINOUS FLUX IN LUMENS	1800/2630/3500/4000/4500/5200/5850/6700	POWER FACTOR	0,9
		LUMEN PER WATT	max.200
		PROTECTION CLASS	II
		VOLTAGE TYPE	DC
		INPUT VOLTAGE SPAN	26-28
		WARRANTY IN YEARS	5
		L80/B10	100000
		DIMMING WITHOUT DIMMER	No
		ENABLED LICENSED PRODUCT	Yes
		INPUT VOLTAGE RANGE LUMINAIRE	26-28
		ASSORTMENT	Proline
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
		LIFETIME L80/B10 AT 25°C	100000
Dimensions			
height:	17mm		
length:	1430mm		
width:	20mm		

ETIM GRUPPEN-ID	EC000996
NO DIM FUNCTION	No
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
FLEXIBLE	Nein
SUITABLE FOR TRAFFIC LIGHTS	No
EXTERNAL DRIVER REQUIRED	Yes
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	Yes
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	350/700/800/900/1050/1200/1400
SHAPE	Rectangular
COLOUR	White