


PRODUCT NO. 1808-350120-B-Ware

DOTLUX LED panel FLATugr 620x620mm 40W 5000K UGR<19 frame white (0-10V dimmable power supply unit included) set of 2



to the product page

Set of 2 consisting of 2x panel and 2x 0-10V dimmable power supply units

Microprism diffuser enables glare-free, homogeneous and shadow-free light distribution
 Fatigue-free working thanks to flicker-free light (= UGR < 19 for VDU workstations)
 Better contrast rendition with very good color rendering and constant color temperature (3-step MacAdam binning)
 High number of low-current LEDs guarantee a long LED service life
 LED service life and consequently low maintenance costs!
 White, powder-coated frame & connection cable with plug connector

WEIGHT IN KG 3.3
POWER CONSUMPTION IN WATTS 40
NET LUMINOUS FLUX IN LUMENS 3900

BEAM ANGLE 120
PROTECTION CLASS (IP) IP40
INPUT VOLTAGE 220 - 240 V AC
SERVICE LIFE approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN 5000
COLOR-RENDERING-INDEX CRI > 83
GLARE-FREE UGR < 19
SWITCH CYCLES > 100.000
WARRANTY IN YEARS 0
DIMMING 1-10 V Yes
DIMMING DALI Yes
DIMMING DMX Yes
DIMMING LINESWITCH Yes
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM Yes
DIMMING MAINS VOLTAGE MODULATION Yes
DIMMING PHASE CUT-OFF Yes
DIMMING PROGRAMMABLE Yes
DIMMING RF Yes
DIMMING ZIGBEE Yes
DIMMING WITH PUSH-BUTTON Yes
DIMMING DEPENDING ON CONTROL GEAR Yes
DIMMING DALI-2 Yes
DIMMING PHASE CUT-ON Yes

Dimensions

length: 620mm
width: 620mm
height: 10mm