

PRODUCT NO. 3487-140170

DOTLUX LED exchangeable module QUICK-FIXplus 11 4 W (2 separate connections) 4000K



to the product page

- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Two independent power supply units guarantee flexible adaptation to existing systems
- Extra high magnetic feet enable installation above the existing cabling
- Our QUICK-FIXplus have DIN EN60598-2-22:2014 certification, which confirms approval in the field of emergency lighting
- Very high efficiency of up to 158 lm/W thanks to low-current LEDs and therefore long service life
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 400 mm
- Both circuits suitable for central battery
- Various power specifications:
 - maximum 15Watt@ 2370 lumen
 - 11W circuit = 1750 lumens
 - 4W circuit = 620 lumens

SUCCESSION ARTICLE	-
PREDECESSOR ARTICLE	3487-040170
WEIGHT IN KG	0.196
NET LUMINOUS FLUX IN LUMENS	2370
LUMEN PER WATT	158
POWER CONSUMPTION IN WATTS	11+4

BEAM ANGLE	170
PROTECTION CLASS (IP)	IP20
TEMPERATURE RANGE	-40°C to +50°C
INPUT VOLTAGE	186 - 240 AC/DC
SERVICE LIFE	approx. 50.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	4000
Lumen per watt	
PROTECTION CLASS	II
VOLTAGE TYPE	AC/DC
SWITCH CYCLES	> 100.000
WARRANTY IN YEARS	3
L80/B10	50000
DIMMING WITHOUT DIMMER	No
ENABLED LICENSED PRODUCT	Yes
ASSORTMENT	Proline
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	D
LIFETIME L80/B10 AT 25°C	50000
LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	100000
ETIM GRUPPEN-ID	EC000096
NO DIM FUNCTION	Yes

Dimensions

diameter: 40mm
height: 180mm

COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
CONNECTION TYPE	Cable
PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471	RG1
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
IFTTT SUPPORT AVAILABLE	No
FLEXIBLE	Nein
SUITABLE FOR TRAFFIC LIGHTS	No
EXTERNAL DRIVER REQUIRED	No
SUITABLE FOR CONSTANT VOLTAGE	No
SUITABLE FOR GENERAL LIGHTING	Yes
SUITABLE FOR CONSTANT CURRENT	No
SUITABLE FOR RAIL TRAFFIC	No
SUITABLE FOR MATRIX INFORMATION BOARDS	No
SUITABLE FOR VARIABLE ROAD SIGNS	No
LIFETIME L70/B50 AT 25°C	100000
LIGHT COLOUR ACCORDING TO EN 12464-1	daylight white >5300 K
BEG FUNDING	Only relevant in Germany
LED-BETRIEBSSTROM IN MA	108
SHAPE	Round
COLOUR	White