

PRODUCT NO. 5061-040090-NOT-B-Ware

DOTLUX LED luminaire insert LINEALock 1437mm 25-75W 4000K dimmable 1-10V 90*110° with emergency lighting module



to the product page

- Glare-reduced 90° PMMA lens optics UGR<21 (2.5-12m light point height)
- Extremely quick mounting thanks to adjustable spring clips
- Environmentally friendly continued use of your existing trunking system
- Independent, integrated cable system (8 x 1.5 mm² incl. emergency lighting charging current) with quick connectors
- Flexible phase selection and power adjustment directly in the luminaire
- Long service life thanks to oversized cooling
- Incl. two safety ropes/mounting aid
- Incl. emergency lighting module with lithium ion battery 3h 1200Lm

Adjustable output with POWERselect:

- 13550lm@ 75W
- 11850lm@ 65W
- 10200lm@ 55W
- 8650lm@ 45W
- 7850lm@ 40W
- 6750lm@ 35W
- 5850lm@ 30W
- 4800lm@ 25W

SUCCESSION ARTICLE	-	BEAM ANGLE	90x110
WEIGHT IN KG	1.99	PROTECTION CLASS (IP)	IP40
POWER CONSUMPTION IN WATTS	25-75	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	13550	INPUT VOLTAGE	186 - 240 AC/DC
LUMEN PER WATT	196-180	Service life	
		OUTPUT LUMEN DURING EMERGENCY	1200
		COLOR TEMPERATURE IN KELVIN	4000
		COLOR-RENDERING-INDEX	CRI > 83
		POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		IK PROTECTION	IK06
		BATTERY RUNTIME	3h
		LUMEN PER WATT	196-180
		HOUSING COLOUR	white
		SWITCH CYCLES	> 100.000
		WARRANTY IN YEARS	0
		L80/B10	100000
		POWER EMERGENCY OPERATION IN W	6.5
		ASSORTMENT	Proline
		LIFETIME L80/B10 AT 25°C	100000

Dimensions

length: 1437mm
width: 67mm
height: 25mm

LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C	200000
DIMMING 1-10 V	Yes
COLOUR CONSISTENCY (MCADAM ELLIPSE)	SDCM6
IMPACT STRENGTH	IK06
LIFETIME L70/B50 AT 25°C	200000
LIFETIME L90/B10 AT 25°C	50000
PULSE DURATION IN µS	0
BEG FUNDING	only relevant in Germany
COLOUR OF LIGHT ADJUSTABLE	No