

PRODUCT NO. 3380-030170-B-Ware

**DOTLUX LED exchangeable module QUICK-FIXplus 24W 3000K-B-goods**



to the product page

- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 120lm/W thanks to low-current LEDs and therefore long service life
- Our QUICK-FIXplus luminaires comply with DIN EN60598-2-22:2014, a standard that confirms approval in the field of emergency lighting.
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 500 mm
- Suitable for central battery
- Tool-free replacement of the LED module even by a non-specialist thanks to AC system plug

<b>SUCCESSION ARTICLE</b>	3380-130170
<b>WEIGHT IN KG</b>	0.36
<b>POWER CONSUMPTION IN WATTS</b>	24
<b>NET LUMINOUS FLUX IN LUMENS</b>	2800
<b>LUMEN PER WATT</b>	117

**Dimensions**

**height:** 35mm  
**diameter:** 240mm

<b>BEAM ANGLE</b>	170
<b>PROTECTION CLASS (IP)</b>	IP20
<b>INPUT VOLTAGE</b>	186 - 240 AC/DC
<b>SERVICE LIFE</b>	approx. 40.000 h at 25°C
<b>COLOR TEMPERATURE IN KELVIN</b>	3000
<b>POWER FACTOR</b>	0,58
<b>LUMEN PER WATT</b>	117
<b>PROTECTION CLASS</b>	II
<b>VOLTAGE TYPE</b>	AC/DC
<b>SWITCH CYCLES</b>	> 80.000
<b>INPUT VOLTAGE SPAN</b>	186-240 V AC/DC
<b>WARRANTY IN YEARS</b>	0
<b>L80/B10</b>	0
<b>DIMMING WITHOUT DIMMER</b>	No
<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	186-240 V AC/DC
<b>LIFETIME L80/B10 AT 25°C</b>	0
<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000
<b>NO DIM FUNCTION</b>	Yes
<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM4
<b>CONNECTION TYPE</b>	Cable
<b>PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471</b>	RG1
<b>COMPATIBLE WITH APPLE HOMEKIT</b>	No
<b>COMPATIBLE WITH GOOGLE ASSISTANT</b>	No
<b>COMPATIBLE WITH AMAZON ALEXA</b>	No

<b>IFTTT SUPPORT AVAILABLE</b>	No
<b>FLEXIBLE</b>	Nein
<b>SUITABLE FOR TRAFFIC LIGHTS</b>	No
<b>EXTERNAL DRIVER REQUIRED</b>	No
<b>SUITABLE FOR CONSTANT VOLTAGE</b>	No
<b>SUITABLE FOR GENERAL LIGHTING</b>	Yes
<b>SUITABLE FOR CONSTANT CURRENT</b>	Yes
<b>SUITABLE FOR RAIL TRAFFIC</b>	No
<b>SUITABLE FOR MATRIX INFORMATION BOARDS</b>	No
<b>SUITABLE FOR VARIABLE ROAD SIGNS</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>LIGHT COLOUR ACCORDING TO EN 12464-1</b>	warm white <3300 K
<b>BEG FUNDING</b>	Only relevant in Germany
<b>LED-BETRIEBSSTROM IN MA</b>	165
<b>SHAPE</b>	Round
<b>COLOUR</b>	Yellow