

PRODUCT NO. 6025-099105-B-Ware

DOTLUX Surface-mounted LED luminaire SOFTEDGE max. 47W COLORselect POWERselect IP44 1500mm DALI B-Goods



to the product page

- Professional wall and ceiling light with large illuminated surface creates a uniform and ceiling-brightening light distribution
- Color-stable and glare-free thanks to prismatic, non-yellowing PMMA diffuser (IK07)
- One luminaire for all performance requirements: POWERSELECT in 4 levels (26W /33W /40W /47W)
- Simply set your favorite color yourself: DOTLUX COLORselect makes it easy to choose between different light colors (3000K/ 4000K/ 6000K)
- Tool-free quick-connect terminal (through-wirable with integrated strain relief)
- Flexible cable entry possible at the back and front
- Simple, flexible installation with 4 different mounting options
- DALI 2.0 certified ballast

| | | | |
|------------------------------------|-------------|--|-----------------|
| SUCCESSION ARTICLE | - | BEAM ANGLE | 105 |
| WEIGHT IN KG | 2.77 | PROTECTION CLASS (IP) | IP44 |
| POWER CONSUMPTION IN WATTS | 26- 47 | LIGHT COLOR | multicoloured |
| NET LUMINOUS FLUX IN LUMENS | 3640 - 6580 | INPUT VOLTAGE | 186 - 240 AC/DC |
| LUMEN PER WATT | 140 | Service life | |
| | | COLOR TEMPERATURE IN KELVIN | 3000/4000/6000 |
| | | COLOR-RENDERING-INDEX | CRI > 82 |
| | | POWER FACTOR | 0,9 |
| | | IK PROTECTION | IK07 |
| | | LUMEN PER WATT | 140 |
| | | PROTECTION CLASS | I |
| Dimensions | | VOLTAGE TYPE | AC |
| length: 1500mm | | HOUSING COLOUR | white |
| width: 150mm | | SUITED FOR EMERGENCY LIGHTING | yes |
| height: 52mm | | INPUT VOLTAGE SPAN | 180-264 |
| | | WARRANTY IN YEARS | 0 |
| | | L80/B10 | 100000 |
| | | RATED CURRENT | 0.13 |
| | | SUITABLE FOR SURFACE MOUNTING | Yes |
| | | SUITABLE FOR MOUNTING | No |
| | | INPUT VOLTAGE RANGE LUMINAIRE | 180-264 |
| | | LIFETIME L80/B10 AT 25°C | 100000 |
| | | LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C | 150000 |
| | | WITH ILLUMINANT | Yes |
| | | SUITABLE FOR WALL MOUNTING | Yes |

| | |
|---|---|
| SUITABLE FOR SUSPENDED MOUNTING | No |
| SUITABLE FOR CEILING MOUNTING | Yes |
| SUITABLE FOR LIGHT LINE CONFIGURATION | Yes |
| SUITABLE FOR WORKPLACE ACCORDING TO EN 12464-1 | No |
| SUITABLE FOR NUMBER OF LIGHT SOURCES | 1 |
| LAMP HOLDER | other Without |
| MATERIAL COVER | Plastic matt/satinized |
| TYPE OF CONTROL GEAR | LED operating device voltage-controlled |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | Yes |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | No |
| DIMMING PHASE CUT-OFF | No |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | Yes |
| DIMMING DEPENDING ON CONTROL GEAR | No |
| NO DIM FUNCTION | No |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM3 |
| DEGREE OF PROTECTION (NEMA) | 2 |
| IMPACT STRENGTH | IK07 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| SUITABLE FOR EMERGENCY LIGHTING | Yes |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| WITH AIR SLOTS | No |
| FILAMENT TEST ACCORDING TO IEC 60695-2-11 | 650 °C - 30 s |
| CONSTANT LIGHT OUTPUT (CLO) | No |
| PHOTOBIOLOGICAL SAFETY ACCORDING TO EN 62471 | RG0 |
| COLOUR OF LIGHT ADJUSTABLE | Positions |
| OPERATION BY BLUETOOTH | No |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |

| | |
|--|-----------------------------|
| IFTTT SUPPORT AVAILABLE | No |
| EXCHANGEABLE CONTROL GEAR | Yes |
| SUITABLE FOR LAMP POWER IN W | 47 |
| LAMP TYPE | LED exchangeable |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| DIMMING DALI-2 | Yes |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| LIFETIME L70/B50 AT 25°C | 150000 |
| LIFETIME L90/B10 AT 25°C | 50000 |
| BEG FUNDING | only relevant in Germany |
| LIGHT OUTLET | Direct |
| TYPE OF WIRING | Suitable for through wiring |
| LUMINOUS FLUX ADJUSTABLE | No |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| SURFACE PROTECTION HOUSING | Powder coating |
| TYPE OF GRID | None |
| LIGHT DISTRIBUTOR | None |
| BEAM ANGLE | Extreme wide beam >80° |
| CONNECTION TYPE | Other |