

PRODUCT NO. 2778

**DOTLUX LED-Downlight CIRCLEclick Treiber nicht dimmbar 6,5 Watt**



to the product page

- <?xml:namespace prefix="o" />+ Optimal für gewerbliche Installationen um Wartungskosten auf ein Minimum zu reduzieren
- + Treiber und Modul je nach Variante einzeln auswechselbar
  - + Wartungsfreundliche, modulare Systemkomponenten
  - + Natürliches Farbempfinden dank des extra hohen CRI-Wertes
  - + Flexible Installationsmöglichkeiten mit vielen Lichtvarianten

<b>SUCCESSION ARTICLE</b>	keiner	<b>PROTECTION CLASS (IP)</b>	IP20
<b>WEIGHT IN KG</b>	0.025	<b>TEMPERATURE RANGE</b>	-40°C to +50°C
		<b>INPUT VOLTAGE</b>	220 - 240 V AC
		<b>SERVICE LIFE</b>	approx. 40.000 h at 25°C
		<b>INRUSH CURRENT IN A</b>	0
		<b>SWITCH CYCLES</b>	> 80.000
<b>Dimensions</b>		<b>INPUT VOLTAGE SPAN</b>	180-250 V AC
<b>length:</b> 46mm		<b>WARRANTY IN YEARS</b>	3
<b>width:</b> 42mm		<b>INPUT VOLTAGE RANGE LUMINAIRE</b>	180-250 V AC
<b>height:</b> 40mm		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>ETIM GRUPPEN-ID</b>	EC001744
		<b>DIMMING 0-10 V</b>	No
		<b>DIMMING 1-10 V</b>	No
		<b>DIMMING DALI</b>	No
		<b>DIMMING DMX</b>	No
		<b>DIMMING DSI</b>	No
		<b>DIMMING POTENTIOMETER (INTEGRATED)</b>	No
		<b>DIMMING LINESWITCH</b>	No
		<b>DIMMING MANUFACTURER'S PROPRIETARY SYSTEM</b>	No
		<b>DIMMING MAINS VOLTAGE MODULATION</b>	No
		<b>DIMMING PHASE CUT-OFF</b>	No
		<b>DIMMING PROGRAMMABLE</b>	No
		<b>DIMMING RF</b>	No

<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>PULSE DURATION IN <math>\mu</math>S</b>	0