

PRODUCT NO. 2782

DOTLUX LED-Downlight CIRCLEclick LED-Modul mit integriertem Treiber nicht dimmbar 2700K 6,5W



to the product page

- Optimal für gewerbliche Installationen um Wartungskosten auf ein Minimum zu reduzieren
- + Treiber und Modul je nach Variante einzeln auswechselbar
 - + Wartungsfreundliche, modulare Systemkomponenten
 - + Natürliches Farbempfinden dank des extra hohen CRI-Wertes
 - + Flexible Installationsmöglichkeiten mit vielen Lichtvarianten

WEIGHT IN KG 0.087

Dimensions

height: 58mm
diameter: 56mm

BEAM ANGLE	38
PROTECTION CLASS (IP)	IP20
TEMPERATURE RANGE	-40°C to +50°C
INPUT VOLTAGE	220 - 240 V AC
SERVICE LIFE	approx. 40.000 h at 25°C
COLOR TEMPERATURE IN KELVIN	2700
COLOR-RENDERING-INDEX	CRI > 92
INRUSH CURRENT IN A	0
SWITCH CYCLES	> 80.000
INPUT VOLTAGE SPAN	180-250 V AC
WARRANTY IN YEARS	3
INPUT VOLTAGE RANGE LUMINAIRE	180-250 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC001744
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No

DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
DREH- /SCHWENKBAR	not swivelling
ADJUSTABILITY	Not adjustable