

PRODUCT NO. 2785

DOTLUX LED downlight CIRCLEcomfort 2700K 6,5W













to the product page

- Glare-free luminaire design especially for hotels and restaurants
- Driver and module individually replaceable with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92
- This luminaire can be upgraded for use as emergency lighting.
- (The battery kit accessories are required)

SUCCESSION ARTICLE	4972-030040	BEAM ANGLE	25
		PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.164	TEMPERATURE RANGE	-40°C
POWER CONSUMPTION IN WATTS	6,5	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	max. 550	SERVICE LIFE	appro
LUMEN PER WATT	85	COLOR TEMPERATURE IN KELVIN	2700
		COLOR-RENDERING-INDEX	CRI > 9
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	85
Dimensions		HOUSING COLOUR	white
		SWITCH CYCLES	> 100.
height: 57mm		INSTALLATION OPENING DIAMETER IN MM	69-88
diameter: 94mm		WARRANTY IN YEARS	3
		ASSORTMENT	Prolin

C to +50°C ox. 50.000 h at 25°C 92 0.000 **ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION** not required 2019/2015 **ETIM GRUPPEN-ID** EC001744 **MATERIAL COVER** Plastic matt/satinized DIMMING DEPENDING ON CONTROL Yes **GEAR** NO DIM FUNCTION No **COLOUR CONSISTENCY (MCADAM** SDCM6 ELLIPSE) **COVERING OF THE LUMINAIRE WITH** THERMALLY INSULATING MATERIAL Yes POSSIBLE PULSE DURATION IN μS 0



BEG FUNDING

DREH- /SCHWENKBAR

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE

COLOUR OF LIGHT ADJUSTABLE

ADJUSTABILITY

Only relevant in Germany swivelling +/-15°

No

Swivelling