

PRODUCT NO. 2800-24

**LED power supply IP67 Proline 24 V/DC, 13.3A, 320 W with MM symbol**



to the product page

LED power supply IP67 High Quality 24 V/DC, 6.3A, 320 W

- **FEATURES:**
  - Universal input
  - overload protection by current limiting, auto recovery
  - protected against short circuit, overload, overvoltage
  - IP67, for indoor and outdoor applications
  - for LED and lighting applications
  - UL1310 Class 2
  - overcurrent shutdown adjustable via internal potentiometer
  - Output voltage adjustable via internal potentiometer
  - EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13
  
- **TECHNICAL DATA:**
  - Input voltage range: 90...264V/AC (47...63Hz) 127...370V/ DC
  - Inrush current max: 65A
  - Overload protection: 95...1080 %.
  - Insulation voltage (I/P-O/P):
  - I/P-O/P: 3750V / AC
  - I/P-EF: 2000V / AC
  - O/P-FG: 500 V / AC
  - Operating temperature range: -30... 70°C
  - Weight: 1000 g

<b>SUCCESSION ARTICLE</b>	-	<b>INRUSH CURRENT IN A</b>	0
<b>WEIGHT IN KG</b>	1.84	<b>ETIM GRUPPEN-ID</b>	EC002710
		<b>NO DIM FUNCTION</b>	Yes
		<b>PULSE DURATION IN µS</b>	0
		<b>BEG FUNDING</b>	Only relevant in Germany

**Dimensions**

**width:** 90mm

**height:** 45mm

**length:** 252mm