

PRODUCT NO. 2775

**DOTLUX LED downlight CIRCLEmini 2700K 3W - Very low installation depth -**



to the product page

- Perfect for renovations due to the low installation depth and large cover
- Driver and module can be replaced individually with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92

<b>SUCCESSION ARTICLE</b>	-	<b>BEAM ANGLE</b>	38
<b>WEIGHT IN KG</b>	0.075	<b>PROTECTION CLASS (IP)</b>	IP20
<b>POWER CONSUMPTION IN WATTS</b>	3	<b>LIGHT COLOR</b>	white
<b>NET LUMINOUS FLUX IN LUMENS</b>	280	<b>SERVICE LIFE</b>	approx. 50.000 h at 25°C
<b>LUMEN PER WATT</b>	93	<b>COLOR TEMPERATURE IN KELVIN</b>	2700
		<b>COLOR-RENDERING-INDEX</b>	CRI > 92
		<b>INRUSH CURRENT IN A</b>	0
		<b>LUMEN PER WATT</b>	93
		<b>HOUSING COLOUR</b>	white
<b>Dimensions</b>		<b>SUITED FOR EMERGENCY LIGHTING</b>	yes
<b>height:</b> 31mm		<b>SWITCH CYCLES</b>	> 100.000
<b>diameter:</b> 75mm		<b>INSTALLATION OPENING DIAMETER IN MM</b>	55-68
		<b>WARRANTY IN YEARS</b>	3
		<b>L80/B10</b>	50000
		<b>ASSORTMENT</b>	Proline
		<b>ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015</b>	not required
		<b>LIFETIME L80/B10 AT 25°C</b>	50000
		<b>LED-LIFETIME LIGHT SOURCE L70/B50 AT 25°C</b>	100000
		<b>ETIM GRUPPEN-ID</b>	EC001744
		<b>MATERIAL COVER</b>	Glass transparent
		<b>DIMMING DEPENDING ON CONTROL GEAR</b>	Yes
		<b>NO DIM FUNCTION</b>	Yes
		<b>COLOUR CONSISTENCY (MCADAM ELLIPSE)</b>	SDCM6

<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE</b>	No
<b>LIFETIME L70/B50 AT 25°C</b>	100000
<b>LIFETIME L90/B10 AT 25°C</b>	25000
<b>PULSE DURATION IN µS</b>	0
<b>BEG FUNDING</b>	Only relevant in Germany
<b>DREH- /SCHWENKBAR</b>	not swivelling
<b>ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE</b>	F
<b>COLOUR OF LIGHT ADJUSTABLE</b>	No
<b>ADJUSTABILITY</b>	Not adjustable