

PRODUCT NO. 2995

DOTLUX Driver not dimmable 3W Suitable only for Art.No.: 2775



to the product page

- Glare-free luminaire design especially for hotels and restaurants
- Driver and module individually replaceable with lockable quick-connect system
- Maintenance-friendly, modular system components
- Natural color perception thanks to extra high CRI value > 92

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP20
WEIGHT IN KG	0.03	INPUT VOLTAGE	176 - 240 V AC/DC
POWER CONSUMPTION IN WATTS	3	OUTPUT CURRENT IN A	0,08
		INRUSH CURRENT IN A	0
		PROTECTION CLASS	II
		SUITED FOR EMERGENCY LIGHTING	yes
		OUTPUT VOLTAGE	32 DC
Dimensions		INPUT VOLTAGE SPAN	180-250 V AC
length: 74mm		WARRANTY IN YEARS	3
width: 38mm		INPUT VOLTAGE RANGE LUMINAIRE	180-250 V AC
height: 25mm		ETIM GRUPPEN-ID	EC002710
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No

DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
SUITABLE FOR EMERGENCY LIGHTING	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
MODEL	-
SUITABLE FOR OUTDOOR USE	No
HOUSING	Plastic housing
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany