

PRODUCT NO. 2813-150120

DOTLUX LED-Lichtbandsystem LINEAclick 65W 5000K breitstrahlend dimmbar DALI Made in Germany



to the product page

- **SCHNELLE MONTAGE**
 - Montage ohne mechanischen Eingriff in das Tragschienensystem mit hitzebeständigen Neodym - Magnethalterungen inkl. Fangseil
 - Einfache Ankopplung an die Stromversorgung aufgrund verschiedener, systemspezifischer Adapterstecker
- **HOHE EFFIZIENZ**
 - Optimierter Transmissionsgrad der LINEACLICK-Linse von DOTLUX®
 - Schattenfreie Lichtverteilung durch innovatives Linsendesign
 - perfekte Kühlung des LED-Moduls dank Alu-Kernplatine
- **WEITERE VORTEILE DER LINEACLICK**
 - Weiterverwendung Ihres vorhandenen Tragschienensystems
 - Verschiedene Linsen für einen breit gefächerten Einsatz
 - Zukunftssicher mit auswechselbarem LED Modul und separatem Treiber
 - LM80 zertifizierte LEDs
 - Notstromtauglich

SUCCESSION ARTICLE	2813-450160	BEAM ANGLE	160
WEIGHT IN KG	1.83	PROTECTION CLASS (IP)	IP20
POWER CONSUMPTION IN WATTS	65	LIGHT COLOR	white
NET LUMINOUS FLUX IN LUMENS	9100	INPUT VOLTAGE	220 - 240 V AC
LUMEN PER WATT	140	SERVICE LIFE	approx. 50.000 h at 25°C
		COLOR TEMPERATURE IN KELVIN	5000
		COLOR-RENDERING-INDEX	CRI > 82
		INRUSH CURRENT IN A	0
		LUMEN PER WATT	140
		VOLTAGE TYPE	AC/DC
Dimensions		HOUSING COLOUR	Aluminium
length: 1530mm		SUITED FOR EMERGENCY LIGHTING	yes
width: 73mm		SWITCH CYCLES	> 100.000
height: 61mm		INPUT VOLTAGE SPAN	198-264 V AC / 176-280 V DC
		WARRANTY IN YEARS	7
		L80/B10	50000
		SUITABLE FOR SURFACE MOUNTING	Yes
		SUITABLE FOR MOUNTING	No
		INPUT VOLTAGE RANGE LUMINAIRE	198-264 V AC / 176-280 V DC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		LIFETIME L80/B10 AT 25°C	50000

ETIM GRUPPEN-ID	EC002892
WITH ILLUMINANT	Yes
SUITABLE FOR SUSPENDED MOUNTING	No
SUITABLE FOR CEILING MOUNTING	No
SUITABLE FOR LIGHT LINE CONFIGURATION	Yes
LAMP HOLDER	-
MATERIAL COVER	Plastic, opal
WITH CONTROL GEAR	Yes
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	Yes
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No
DIMMING PHASE CUT-OFF	No
DIMMING PROGRAMMABLE	No
DIMMING RF	No
DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	Yes
NO DIM FUNCTION	No
LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24	No
SUITABLE FOR EMERGENCY LIGHTING	Yes
WITH MOVEMENT SENSOR	No
WITH LIGHT SENSOR	No
CONSTANT LIGHT OUTPUT (CLO)	No
TYPE OF WIRING	Through wiring included
CONNECTION TYPE	Bus
OPERATION BY BLUETOOTH	No
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
EXCHANGEABLE CONTROL GEAR	Yes
SUITABLE FOR LAMP POWER IN W	65
LAMP TYPE	LED
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN µS	0
ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE	D
LIGHT SHARING	Asymmetric
LIGHT OUTLET	Direct
COLOUR OF LIGHT ADJUSTABLE	No
BEAM ANGLE ADJUSTABLE	No

LUMINOUS FLUX ADJUSTABLE	Continuously variable
TYPE OF GRID	Other
LIGHT DISTRIBUTOR	Other
SURFACE PROTECTION HOUSING	Other
BEAM ANGLE	Extreme wide beam >80°