

PRODUCT NO. 3143-24

LED power supply IP67 Proline 24 V/DC, 25A, 600W with MM mark



to the product page

LED Power Supply IP67 High Quality 24 V/DC, 25A, 600 W

- **FEATURES:**
 - Universal input
 - overload protection by current limiting, auto recovery
 - protected against short circuit, overload, overvoltage
 - IP67, for indoor and outdoor applications
 - for LED and lighting applications
 - UL1310 Class 2
 - dimmable
 - EN61000-3-2, Class C, EN55015, EN61347-1, EN61347-2-13

- **TECHNICAL DATA:**
 - Input voltage range: 90...264V/AC (47...63Hz) 127...370V/ DC
 - Inrush current max: 65A
 - Overload protection: 95...1080 %.
 - Insulation voltage (I/P-O/P):
 - I/P-O/P: 3750V / AC
 - I/P-EF: 2000V / AC
 - O/P-FG: 500 V / AC
 - Operating temperature range: -30... 70°C
 - Weight: 1000 g

SUCCESSION ARTICLE	-	INRUSH CURRENT IN A	0
WEIGHT IN KG	3.748	ETIM GRUPPEN-ID	EC002710
		NO DIM FUNCTION	No
		COMPATIBLE WITH CASAMBI	No
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
Dimensions		COMPATIBLE WITH AMAZON ALEXA	No
width: 144mm		PULSE DURATION IN µS	0
height: 49mm		BEG FUNDING	Only relevant in Germany
length: 280mm			