

PRODUCT NO. 3487

DOTLUX QUICK-FIXplus 16 4 W warm white 3000K LED interchangeable module (with 4 W emergency lighting module with separate connection)













to the product page



- Universal MAGNET LED module with integrated driver for quick and easy replacement of light sources in existing ceiling and wall luminaires
- Extra high magnetic feet enable installation above the existing cabling
- Very high efficiency of up to 120lm/W thanks to low-current LEDs and therefore long service life
- Our QUICK-FIXplus luminaires comply with DIN EN60598-2-22:2014, a standard that confirms approval in the field of emergency lighting.
- Special lenses with 170° beam angle ensure absolutely shadow-free light distribution even in larger luminaires up to 400mm
- Integrated 4W emergency lighting module with separate power supply unit suitable for central battery

WEIGHT IN KG 0.2

POWER CONSUMPTION IN WATTS 16 + 4

NET LUMINOUS FLUX IN LUMENS 1900 / 450

LUMEN PER WATT 119

Dimensions

height: 68mm diameter: 180mm BEAM ANGLE 170
PROTECTION CLASS (IP) IP40
TEMPERATURE RANGE -40°C

 TEMPERATURE RANGE
 -40°C to +50°C

 INPUT VOLTAGE
 186 - 240 AC/DC

 SERVICE LIFE
 approx. 40.000 h at 25°C

 COLOR TEMPERATURE IN KELVIN
 3000

 LUMEN PER WATT
 119

 PROTECTION CLASS
 II

 VOLTAGE TYPE
 AC/DC

 SWITCH CYCLES
 > 80.000

 INPUT VOLTAGE SPAN
 186-240 AC/DC

WARRANTY IN YEARS

INPUT VOLTAGE RANGE LUMINAIRE 186-240 AC/DC

EC000996

SDCM4

Cable

RG1

Yes

No

ENERGY EFFICIENCY CLASS
ACCORDING TO EU REGULATION

2019/2015

ETIM GRUPPEN-ID

COLOUR CONSISTENCY (MCADAM

ELLIPSE)

CONNECTION TYPE
PHOTOBIOLOGICAL SAFETY
ACCORDING TO EN 62471

COMPATIBLE WITH APPLE HOMEKIT
COMPATIBLE WITH GOOGLE

ASSISTANT

COMPATIBLE WITH AMAZON ALEXA No IFTTT SUPPORT AVAILABLE No



FLEXIBLE Nein SUITABLE FOR TRAFFIC LIGHTS No **EXTERNAL DRIVER REQUIRED** No SUITABLE FOR CONSTANT VOLTAGE No SUITABLE FOR GENERAL LIGHTING Yes SUITABLE FOR CONSTANT CURRENT No SUITABLE FOR RAIL TRAFFIC No SUITABLE FOR MATRIX INFORMATION No **BOARDS** SUITABLE FOR VARIABLE ROAD SIGNS No

SOLIABLE FOR VARIABLE ROAD SIGN

LIGHT COLOUR ACCORDING TO EN 12464-1

warm white <3300 K

BEG FUNDING Only relevant in Germany

LED-BETRIEBSSTROM IN MA 110-40
SHAPE Round
COLOUR Yellow