

PRODUCT NO. 3574

DOTLUX Standardnetzteil für DOTLUX LED-Panel 50 Watt 1200mA (für Art. 3572-040120)



to the product page

PREDECESSOR ARTICLE	1688
WEIGHT IN KG	0.22
POWER CONSUMPTION IN WATTS	50

**Dimensions**

**length:** 155mm  
**width:** 53mm  
**height:** 30mm

PROTECTION CLASS (IP)	IP20
INPUT VOLTAGE	220 - 240 V AC
OUTPUT CURRENT IN A	1,25
POWER FACTOR	0,95
TC TEMPERATURE IN °C	80
PROTECTION CLASS	II
SUITED FOR EMERGENCY LIGHTING	yes
OUTPUT VOLTAGE	27 - 42 DC
INPUT VOLTAGE SPAN	220-240 V AC
WARRANTY IN YEARS	5
SUITED FOR EMERGENCY POWER	-
INPUT VOLTAGE RANGE LUMINAIRE	220-240 V AC
ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
ETIM GRUPPEN-ID	EC002710
DIMMING 0-10 V	No
DIMMING 1-10 V	No
DIMMING DALI	No
DIMMING DMX	No
DIMMING DSI	No
DIMMING POTENTIOMETER (INTEGRATED)	No
DIMMING LINESWITCH	No
DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
DIMMING MAINS VOLTAGE MODULATION	No

<b>DIMMING PHASE CUT-OFF</b>	No
<b>DIMMING PROGRAMMABLE</b>	No
<b>DIMMING RF</b>	No
<b>DIMMING SINE WAVE REDUCTION</b>	No
<b>DIMMING TOUCH AND DIM</b>	No
<b>DIMMING ZIGBEE</b>	No
<b>DIMMING WITH PUSH-BUTTON</b>	No
<b>DIMMING DEPENDING ON CONTROL GEAR</b>	No
<b>NO DIM FUNCTION</b>	Yes
<b>SUITABLE FOR EMERGENCY LIGHTING</b>	Yes
<b>DIMMING DALI-2</b>	No
<b>DIMMING PHASE CUT-ON</b>	No
<b>DIMMING GPRS</b>	No
<b>LED-BETRIEBSSTROM IN MA</b>	1200