

PRODUCT NO. 3941-040IP205M

DOTLUX LED strip 24W 8mm 4000K IP20 5m roll incl. 50cm connection cable on both sides












to the product page

- Cozy and natural light due to extra high color rendering RA>92
- Consistent color temperature due to 3-step Mac Adam binning
- Very densely arranged LEDs enable homogeneous luminous surfaces at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder joints
- Reinforced conductor paths ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 15 cm connection cable pre-mounted on one side



SUCCESSION ARTICLE	-	BEAM ANGLE	120
PREDECESSOR ARTICLE	1982-2	PROTECTION CLASS (IP)	IP20
		LIGHT COLOR	white
WEIGHT IN KG	0.35	SERVICE LIFE	approx
POWER CONSUMPTION IN WATTS	24	COLOR TEMPERATURE IN KELVIN	4000
NET LUMINOUS ELLIY IN LUMENS	2100	COLOD-DENDEDING-INDEX	CDI > 0

Dimensions

length: 5000mm width: 8mm height: 1mm

ox. 50.000 h at 25°C CRI > 92 100 **SEVERABLE BY MM** TC TEMPERATURE IN °C 67 OUTPUT W/M 4,8 LIGHT FLUX LM/M 420 SMALLEST BEND RADIUS IN MM 25 INPUT VOLTAGE SPAN 24 V DC WARRANTY IN YEARS INPUT VOLTAGE RANGE LUMINAIRE 24 V DC **ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION** 2019/2015

ETIM GRUPPEN-ID EC002706

COMPATIBLE WITH APPLE HOMEKIT No

COMPATIBLE WITH GOOGLE NO

ASSISTANT

COMPATIBLE WITH AMAZON ALEXA No

BEG FUNDING Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE

COLOUR OF LIGHT ADJUSTABLE

No