

PRODUCT NO. 3942-027IP205M


weighter und her state and the second of the second state of the second state of the second state of the second

DOTLUX LED strip 48W 8mm 2700K IP20 5m roll incl. 50cm connection cable both sides

IP 20 120 **Z**JAHRE DOTLUX



to the product page



- Cozy and natural light due to extra high color rendering RA>92
- Consistent color temperature due to 3-step Mac Adam binning
- Very densely arranged LEDs enable homogeneous luminous surfaces at smallest distances
- Secure Solder Connect Technology prevents hairline cracks and cold solder joints
- Reinforced conductor tracks ensure uniform brightness
- Original 3M adhesive tape provides strong hold
- 50 cm connection cable pre-mounted on both sides

SUCCESSION ARTICLE	-	BEAM ANGLE	120
PREDECESSOR ARTICLE	1979-2	PROTECTION CLASS (IP)	IP20
		LIGHT COLOR	white
WEIGHT IN KG	0.12	SERVICE LIFE	approx. 50.000 h at 25°C
POWER CONSUMPTION IN WATTS	48	COLOR TEMPERATURE IN KELVIN	2700
NET LUMINOUS FLUX IN LUMENS	4000	COLOR-RENDERING-INDEX	CRI > 92
		AMOUNT OF LED/M	140
		SEVERABLE BY MM	50
		OUTPUT W/M	9,6
Dimensions		LIGHT FLUX LM/M	800
		SMALLEST BEND RADIUS IN MM	25
width: 8mm		INPUT VOLTAGE SPAN	24 V DC
length: 5000mm		WARRANTY IN YEARS	7
height: 2mm		INPUT VOLTAGE RANGE LUMINAIRE	24 V DC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	F
		ETIM GRUPPEN-ID	EC002706
		COMPATIBLE WITH APPLE HOMEKIT	No
		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No

BEG FUNDING

ENERGIEEFFIZIENZKLASSE DER LICHTQUELLE EINER LEUCHTE COLOUR OF LIGHT ADJUSTABLE

No

Only relevant in Germany