


PRODUCT NO. 4193-03050120FB

DOTLUX LED hall floodlight LIGHTSHOWRevo-ambient 135W 5000K DALI 35W 3000K phase cut dimmable frosted ball proof Made in Germany



to the product page

- Unique: Two luminaires in one: 22,000 lumens daylight white with 5,000 K in the center, surrounded by a 5,600 lumen ring with 3000 K warm white light, Made in Germany
- Ball impact resistant according to DIN 18032-3:1997-04 and DIN57710-13:1981-05
- Dimension: 370 x 130 mm
- Color rendering (Ra): > 85 (5,000 K) / > 82 (3,000K)
- Input voltage: 110-240 V AC /176-276 V DC (DALI) 220-240 V AC (phase cut-off)
- Power consumption: max. 135 W (5,000 K operation) / max. 35 W (3,000 K operation)
- Service life: > 80,000 h at 60 °C
- DALI dimmable (5,000 K portion)
- Phase angle dimming (3,000 K component)
- Sustainable product design due to easily replaceable components

| | | | |
|------------------------------------|---------------------------------------|--|--------------------------|
| SUCCESSION ARTICLE | - | BEAM ANGLE | 120 |
| WEIGHT IN KG | 5.9 | PROTECTION CLASS (IP) | IP40 |
| POWER CONSUMPTION IN WATTS | max.135 bei 5000K, (max.35 bei 3000K) | LIGHT COLOR | white |
| NET LUMINOUS FLUX IN LUMENS | 20000 bei 5000K (4600 bei 3000K) | INPUT VOLTAGE | 176 - 240 V AC/DC |
| LUMEN PER WATT | 148 (131 bei 3000K) | SERVICE LIFE | approx. 80.000 h at 60°C |
| Dimensions | | COLOR TEMPERATURE IN KELVIN | 3000/5000 |
| diameter: 380mm | | COLOR-RENDERING-INDEX | CRI > 85 |
| length: 380mm | | POWER FACTOR | 0,98 |
| height: 165mm | | INRUSH CURRENT IN A | 0 |
| width: 380mm | | LUMEN PER WATT | 148 (131 at 3000K) |
| | | PROTECTION CLASS | I |
| | | VOLTAGE TYPE | AC/DC |
| | | SUITED FOR EMERGENCY LIGHTING | No |
| | | BALLPROOF | yes |
| | | SWITCH CYCLES | > 160.000 |
| | | FOOD-READY | Yes |
| | | INSTALLATION OPENING WIDTH IN MM | 0 |
| | | INSTALLATION OPENING DIAMETER IN MM | 0 |
| | | INSTALLATION OPENING LENGHT IN MM | 0 |
| | | INPUT VOLTAGE SPAN | 180-295 V AC |
| | | WARRANTY IN YEARS | 7 |
| | | L80/B10 | 80000 |
| | | SUITABLE FOR MOUNTING | No |
| | | DIMMING WITHOUT DIMMER | No |

| | |
|--|----------------------------|
| INPUT VOLTAGE RANGE LUMINAIRE | 180-295 V AC |
| ASSORTMENT | Highline |
| ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015 | not required |
| LIFETIME L80/B10 AT 25°C | 80000 |
| ETIM GROUP IDENTIFICATION NUMBER | EC001744 |
| WITH ILLUMINANT | Yes |
| SUITABLE FOR WALL MOUNTING | No |
| SUITABLE FOR SUSPENDED MOUNTING | Yes |
| SUITABLE FOR CEILING MOUNTING | Yes |
| LAMP HOLDER | other Without |
| MATERIAL COVER | Plastic, opal |
| WITH CONTROL GEAR | Yes |
| DIMMING 0-10 V | No |
| DIMMING 1-10 V | No |
| DIMMING DALI | Yes |
| DIMMING DMX | No |
| DIMMING DSI | No |
| DIMMING POTENTIOMETER (INTEGRATED) | No |
| DIMMING LINESWITCH | No |
| DIMMING MANUFACTURER'S PROPRIETARY SYSTEM | No |
| DIMMING MAINS VOLTAGE MODULATION | Yes |
| DIMMING PHASE CUT-OFF | Yes |
| DIMMING PROGRAMMABLE | No |
| DIMMING RF | No |
| DIMMING SINE WAVE REDUCTION | No |
| DIMMING TOUCH AND DIM | No |
| DIMMING ZIGBEE | No |
| DIMMING WITH PUSH-BUTTON | No |
| DIMMING DEPENDING ON CONTROL GEAR | Yes |
| NO DIM FUNCTION | No |
| COLOUR CONSISTENCY (MCADAM ELLIPSE) | SDCM6 |
| LUMINAIRE WITH LIMITED SURFACE TEMPERATURE, SIGN "D" ACCORDING TO EN 60598-2-24 | Yes |
| SUITABLE FOR EMERGENCY LIGHTING | No |
| WITH MOVEMENT SENSOR | No |
| WITH LIGHT SENSOR | No |
| COVERING OF THE LUMINAIRE WITH THERMALLY INSULATING MATERIAL POSSIBLE | No |
| TYPE OF WIRING | Ending |
| CONNECTION TYPE | sonstige Offene Kabelenden |
| COLOUR OF LIGHT ADJUSTABLE | Positions |
| OPERATION BY BLUETOOTH | No |
| COMPATIBLE WITH CASAMBI | No |
| COMPATIBLE WITH APPLE HOMEKIT | No |
| COMPATIBLE WITH GOOGLE ASSISTANT | No |
| COMPATIBLE WITH AMAZON ALEXA | No |
| IFTTT SUPPORT AVAILABLE | No |
| SUITABLE FOR LOW VOLTAGE CABLE SYSTEM | No |
| SUITABLE FOR CLAMP-MOUNTING | No |

| | |
|---|--------------------------|
| SUITABLE FOR LIGHT-TRACK MOUNTING | No |
| SUITABLE FOR PEDESTAL/FLOOR MOUNTING | No |
| SUITABLE FOR TRAVERSE MOUNTING | No |
| EXCHANGEABLE CONTROL GEAR | Yes |
| SUITABLE FOR LAMP POWER IN W | 135 + 35 |
| LAMP TYPE | LED exchangeable |
| EMERGENCY POWER SUPPLY INTEGRATED | No |
| SURFACE BRUSHED | No |
| DIMMING DALI-2 | No |
| DIMMING PHASE CUT-ON | No |
| DIMMING GPRS | No |
| PULSE DURATION IN µS | 0 |
| BEG FUNDING | only relevant in Germany |
| ENERGY EFFICIENCY CLASS OF THE LIGHT SOURCE OF A LUMINAIRE | - |
| LIGHT OUTLET | Direct |
| BEAM ANGLE ADJUSTABLE | No |
| LIGHT SHARING | Symmetric |
| LUMINOUS FLUX ADJUSTABLE | Continuously variable |
| SURFACE PROTECTION | Powder coating |
| ADJUSTABILITY | Not adjustable |
| REFLECTOR | None |
| HOUSING COLOUR | silver |
| LIGHT DISTRIBUTOR | None |
| BEAM ANGLE | Extreme wide beam >80° |