

PRODUCT NO. 1964-0601605

DOTLUX LED module ADplus 0,72W 12V 160° IP65 6000K 20pcs chain










to the product page



- Input voltage: 12 V DC
- LED module ADplus is delivered ready wired as a chain of 20 modules!
- Technically, up to 2 chains (á 20 modules) can be wired in series.
- A parallel connection of several chains is possible for the uniform illumination of larger larger areas without any problems.

TIP:In order to extend the maintenance cycle of the power supply it is recommended to design the power supply with approx. 20% more power than required. than required.



SUCCESSION ARTICLE PREDECESSOR ARTICLE	- 1964
WEIGHT IN KG	1.35
NET LUMINOUS FLUX IN LUMENS	60
LUMEN PER WATT	86

Dimensions

length: 70mm width: 15mm height: 7mm

BEAM ANGLE	160
PROTECTION CLASS (IP)	IP65
TEMPERATURE RANGE	-40°C to +40°C
LIGHT COLOR	white
SERVICE LIFE	approx. 50.000 h at 25°0
COLOR TEMPERATURE IN KELVIN	6000
COLOR-RENDERING-INDEX	CRI > 80
LUMEN PER WATT	86
PROTECTION CLASS	III
SELF-STICKING	yes
SWITCH CYCLES	> 100.000
INPUT VOLTAGE SPAN	12 V DC
WARRANTY IN YEARS	5
INPUT VOLTAGE RANGE LUMINAIRE	12 V DC
CHERCY CECICIONICY CLASS	

ENERGY EFFICIENCY CLASS
ACCORDING TO EU REGULATION G
2019/2015

ETIM GRUPPEN-ID EC002706

COMPATIBLE WITH APPLE HOMEKIT No

COMPATIBLE WITH GOOGLE
ASSISTANT No

COMPATIBLE WITH AMAZON ALEXA No

BEG FUNDING Only relevant in Germany

ENERGIEEFFIZIENZKLASSE DER
LICHTQUELLE EINER LEUCHTE

COLOUR OF LIGHT ADJUSTABLE

No