

## **PRODUCT NO.** 4252-24

## LED power supply unit CV 24V DC 75W 3.15A IP67





to the product page



- The LED power supply units in an IP67 aluminum housing are used for LED and lighting applications.
- Overload protection by switching off
- Suitable for constant current and constant voltage

SUCCESSION ARTICLE	-	PROTECTION CLASS (IP)	IP67
		INPUT VOLTAGE	176 - 240 V AC/DC
WEIGHT IN KG	0.674	OUTPUT CURRENT IN A	3,15
POWER CONSUMPTION IN WATTS	75	INRUSH CURRENT IN A	0
		TC TEMPERATURE IN °C	85
		OUTPUT VOLTAGE	24 DC
		INPUT VOLTAGE SPAN	100-305 AC / 142-431 DC
Dimensions		INPUT VOLTAGE RANGE LUMINAIRE	100-305 AC / 142-431 DC
		ETIM GRUPPEN-ID	EC002710
length: 243mm		DIMMING 0-10 V	No
width: 71mm		DIMMING 1-10 V	No
height: 37mm		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	Νο
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	Νο
		DIMMING MAINS VOLTAGE MODULATION	Νο
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No



DIMMING WITH PUSH-BUTTON	No
NO DIM FUNCTION	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN $\mu$ S	0
BEG FUNDING	Only relevant in Germany