


PRODUCT NO. 4255-24

LED power supply CV 24V/DC 240W 10A IP20 for DIN rail mounting



to the product page

- Switching power supply for DIN rail mounting
- LED display for DC OK.
- due to the closed design the screw terminals are protected against accidental contact
- overload protection by current limitation

SUCCESSION ARTICLE	-	INPUT VOLTAGE	176 - 240 V AC/DC
WEIGHT IN KG	0.92	OUTPUT CURRENT IN A	10
POWER CONSUMPTION IN WATTS	240	POWER FACTOR	0,95
		INRUSH CURRENT IN A	0
		OUTPUT VOLTAGE	24 DC
		INPUT VOLTAGE SPAN	90-264 AC / 127-370 DC
		INPUT VOLTAGE RANGE LUMINAIRE	90-264 AC / 127-370 DC
		ETIM GROUP IDENTIFICATION NUMBER	ECC002710
Dimensions		DIMMING 0-10 V	No
length: 114mm		DIMMING 1-10 V	No
width: 63mm		DIMMING DALI	No
height: 125mm		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No
		DIMMING SINE WAVE REDUCTION	No
		DIMMING TOUCH AND DIM	No
		DIMMING ZIGBEE	No
		DIMMING WITH PUSH-BUTTON	No

NO DIM FUNCTION	Yes
COMPATIBLE WITH CASAMBI	No
COMPATIBLE WITH APPLE HOMEKIT	No
COMPATIBLE WITH GOOGLE ASSISTANT	No
COMPATIBLE WITH AMAZON ALEXA	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0
BEG FUNDING	Only relevant in Germany