

PRODUCT NO. 4256-24

LED power supply CV 24V/DC 100W 4A IP20 for DIN rail mounting







to the product page

- Single-phase switching power supply for DIN rail mounting
- touch-protected screw connections due to closed design
- Current limitation of the power supply enables overload protection

SUCCESSION ARTICLE	-	INPUT VOLTAGE	176 - 240 V AC/DC
		OUTPUT CURRENT IN A	4
WEIGHT IN KG	0.398	POWER FACTOR	0,95
POWER CONSUMPTION IN WATTS	100	INRUSH CURRENT IN A	0
		OUTPUT VOLTAGE	24 DC
		INPUT VOLTAGE SPAN	85-264 AC / 120-370 DC
		INPUT VOLTAGE RANGE LUMINAIRE	85-264 AC / 120-370 DC
Dimensions		ETIM GRUPPEN-ID	EC002710
		NO DIM FUNCTION	Yes
length: 100mm		COMPATIBLE WITH CASAMBI	No
width: 55mm		COMPATIBLE WITH APPLE HOMEKIT	No
height: 90mm		COMPATIBLE WITH GOOGLE ASSISTANT	No
		COMPATIBLE WITH AMAZON ALEXA	No
		PULSE DURATION IN µS	0
		BEG FUNDING	Only relevant in Germany