

PRODUCT NO. 4323

DOTLUX Netzteil 150W 48V 3,13A CV+CC



to the product page

the power supply supports constant current and constant voltage output in dual mode.

Thanks to the 91% high efficiency and fanless design, the series can operate under free air convection in the temperature range of -40°C to +90°C. IP65 protection class due to intelligent design and aluminum housing.

SUCCESSION ARTICLE	kein NF - Sortimenststraffung	PROTECTION CLASS (IP)	IP65
WEIGHT IN KG	0.87	FREQUENCY RANGE IN HZ	47-63
POWER CONSUMPTION IN WATTS	105	OUTPUT CURRENT IN A	3,13
		POWER FACTOR	0,97
		INRUSH CURRENT IN A	0
		PROTECTION CLASS	I
Dimensions		OUTPUT VOLTAGE	48 DC
width: 63mm		INPUT VOLTAGE SPAN	100-305 AC / 142-431 DC
height: 36mm		WARRANTY IN YEARS	3
length: 220mm		INPUT VOLTAGE RANGE LUMINAIRE	100-305 AC / 142-431 DC
		ENERGY EFFICIENCY CLASS ACCORDING TO EU REGULATION 2019/2015	not required
		DIMMING 0-10 V	No
		DIMMING 1-10 V	No
		DIMMING DALI	No
		DIMMING DMX	No
		DIMMING DSI	No
		DIMMING POTENTIOMETER (INTEGRATED)	No
		DIMMING LINESWITCH	No
		DIMMING MANUFACTURER'S PROPRIETARY SYSTEM	No
		DIMMING MAINS VOLTAGE MODULATION	No
		DIMMING PHASE CUT-OFF	No
		DIMMING PROGRAMMABLE	No
		DIMMING RF	No

DIMMING SINE WAVE REDUCTION	No
DIMMING TOUCH AND DIM	No
DIMMING ZIGBEE	No
DIMMING WITH PUSH-BUTTON	No
DIMMING DEPENDING ON CONTROL GEAR	No
NO DIM FUNCTION	Yes
DIMMING DALI-2	No
DIMMING PHASE CUT-ON	No
DIMMING GPRS	No
PULSE DURATION IN μS	0